



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

F2X4LG6 2" X 4" Slotted Wiring Duct, Gray

Panduit Corporation

Catalog Number	F2X4LG6
Manufacturer	Panduit Corporation
Description	The F2X4LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct Features A Narrow Slot/Finger Design That Closely Matches The Spacing Of High-Density Components. Upper and Lower Scorelines Allow For Easy Finger/Sidewall Section Removal. UL 94 Flame Class Of V-0 With A UL Recognized Continuous-Use Temperature Up To 122°F (50°C). Mounting Holes Provided. Lead-Free PVC. 2" X 4" (50.8 MM X 101.6 MM) and 6' (1.83 M) Long. Cover Sold Separately. Color Light Gray.
Weight per unit	0.4660 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

Features

media	Yes
-------	-----

Descriptions

Description	2" X 4" SLOTTED WIRING DUCT, GRAY
extra long description	PAN F2X4LG6 Panduct® F2X4LG6 Base W
Long Description	The F2X4LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 2" x 4" (50.8 mm x 101.6 mm) and 6' (1.83 m) long. Cover sold separately. Color Light Gray.
Product Type	Panduct® F2X4LG6 Base Wiring Duct

Manufacturer Information

Brand	PANDUIT
GTIN	00074983375615
Manufacturers Part Number	F2X4LG6
UPC	074983375615

Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
----------------------	----------------------

Availability

minimum qty	6
-------------	---



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	6
Package	60
Weight Per foot	0.466