



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1026 North Collins Blvd  
70433-0000, LA Covington  
Phone: 985-302-3016  
Fax: 985-249-6076

## F84T12DH0 100W T12 84" Daylight High Output 76 Cri R17D

*Sylvania-Ledvance*

|                  |                                                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------|
| Catalog Number   | F84T12DH0                                                                                                      |
| Manufacturer     | Sylvania-Ledvance                                                                                              |
| Description      | 100W, 84" Mol, T12 Ho (800 Ma) Rapid Start Fluorescent Lamp, Daylightphosphor, 6500K Color Temperature, 72 Cri |
| Weight per unit  | 1.3 (lbs/each)                                                                                                 |
| Product Category | Linear Fluorescent Straight La                                                                                 |

### Features

|                           |                                     |
|---------------------------|-------------------------------------|
| amperage rating           | Ballast Dependent                   |
| average life              | 12000                               |
| Base                      | Recessed Double Contact             |
| bulb type                 | T12                                 |
| lumens                    | 6700 Initial Lumens at 25 Degrees C |
| Shape                     | T12                                 |
| start type                | Rapid Start                         |
| total harmonic distortion | Ballast Dependent                   |
| Voltage Rating            | Ballast Dependent                   |
| Wattage                   | 100                                 |

### Material, Color, and Finish

|                             |                 |
|-----------------------------|-----------------|
| color rendering index (cri) | 76              |
| color temperature           | 6500            |
| Finish                      | Phosphor Coated |

### Dimensions and Weight

|          |        |
|----------|--------|
| Diameter | 1.5 in |
|----------|--------|

### Descriptions

|                        |                                                                                                                |
|------------------------|----------------------------------------------------------------------------------------------------------------|
| Description            | 100W T12 84" DAYLIGHT HIGH OUTPUT 76 CRI R17D                                                                  |
| extra long description | SYL F84T12DHO/25385 F84T12DHO 15/CS                                                                            |
| Long Description       | 100W, 84" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Daylightphosphor, 6500K color temperature, 72 CRI |
| Product Type           | F84T12DHO 15/CS 1/Sku                                                                                          |

### Manufacturer Information

|                           |                   |
|---------------------------|-------------------|
| Brand                     | SYLVANIA          |
| GTIN                      | 00046135253850    |
| Manufacturers Part Number | F84T12/D/HO/25385 |
| UPC                       | 046135253850      |

### Taxonomies, Classifications, and Categories

|                      |             |
|----------------------|-------------|
| Category Description | Fluorescent |
| Type                 | FLUORESCENT |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1026 North Collins Blvd  
70433-0000, LA Covington  
Phone: 985-302-3016  
Fax: 985-249-6076

## Packaging

|                 |      |
|-----------------|------|
| Carton          | 1    |
| Package         | 15   |
| Weight Per each | 1.26 |

## Uses, Certifications, and Standards

|             |                        |
|-------------|------------------------|
| Application | Commercial/Residential |
|-------------|------------------------|