



FAN & FIXTURE BOXES

FOR A VARIETY OF USES




Choose the Fan or Fixture Box that's right for you...


...in Steel or Plastic – or a Combination!

No matter what your needs – or installation preferences, Arlington has a fan/fixture box to fit.

We manufacture a variety of steel and non-metallic boxes in many depths and cubic inch capacities that install directly to the joist(s) for an extra-secure installation.



Our boxes that mount to the bottom of a joist deliver a safe, secure installation because both the box and the bracket install directly to the joist!



Plus, we have a box for every ceiling condition!


Joist Mount

page 4

FBS405, FBS405T
6.0 cubic inches
FBS407, FBS407T
8.0 cubic inches



for NEW CONSTRUCTION



Under-Joist Mount

page 5

FBS415
1-1/2" depth
14.6 cubic inches
FBS420
2" depth
20.0 cubic inches



For NEW CONSTRUCTION



Side Mount

page 5

FBS415S
1-1/2" depth
14.6 cubic inches
FBS420S
2" depth
20.0 cubic inches



For NEW CONSTRUCTION



page 14

FBS1423
23.0 cubic inches

For NEW and Existing CONSTRUCTION

Mounts Between Joists Adjustable Brackets

pages 6-7


FBR415
15.6 cubic inches

For NEW CONSTRUCTION

FBR407R
8.0 cubic inches

For RETROFIT

FBR420R
2" depth
20.0 cubic inches



For Any Suspended Ceiling Frame

page 8

FBR420SC, FS420SCL
2" depth
20.0 cubic inches

Steel



FB405
6.0 cubic inches
FB407
8.0 cubic inches
FB412
14.4 cubic inches



Plastic

Joist Mount

page 10

FB415
10.3 cubic inches
FB423
19.5 cubic inches
FB426
16.0 cubic inches



Press Hold Joist Mount

page 11

FB442
13.4 cubic inches
FB443
17.96 cubic inches
FB444
25.6 cubic inches



Side Mount

page 12

Steel & Plastic

FB417S
20.0 cubic inches
Low profile
FB417SLP
20.0 cubic inches



Side Mount Plastic Box with Steel Bracket

page 13

MB8
6.1 cubic inches



8" Mounting Block

page 14

Each of our boxes is UL Listed to hold fans and fixtures of a specific weight; generally from 35 to 200 lbs., depending on the box. In addition, our non-metallic boxes offer a 2-hour fire rating.



For ceilings up to 1-1/2" thick.

Applications include:

- 1/2" or 5/8" drywall
- Double drywall
- Drywall mounted to hat channel, or furring strips, then to the joist
- Single or double joists



Most of Arlington's fan boxes ship with an installed NM cable connector, mud cover in place and captive installation screws for both the box and the fan/fixture mounting bracket.



Arlington's fan/fixture boxes are patented (or other patents pending).



FBS405
for 1/2" and 5/8" drywall

FBS407
for 5/8" drywall

Designed for 1/2" or 5/8" drywall ceilings, our cost-effective, plated steel FBS405 and FBS407 pan boxes mount directly to a ceiling joist for a super-secure installation.

- For NEW CONSTRUCTION
- UL Rated for 70 lb. fans; 200 lb. fixtures
- CSA Rated for 50 lb. fan or fixture

Protective plastic tips

Installed mud cover

Captive installation screws remain in place until used

Installed NM cable connector

Green ground screw

FBS405T
inside view

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Ceiling Thickness	Unit/Std Pkg
FBS405	76185	6.0	1/2", 5/8"	25
FBS407	76187	8.0	5/8"	25
*FBS405T	40500	6.0	1/2", 5/8"	25
*FBS407T	40700	8.0	5/8"	25

* with threaded openings and #10 screws (supplied) for mounting fan/fixture bracket.

1 Secure installation! Box mounts directly to joist with captive screw near center.

2 Convenient. Drill (2) 1/8" dia. holes into joist through elongated openings on each side of box. Remove the (2) screws noted above. Use to mount the bracket...

3 Easy. Mount bracket into the holes with the (2) long screws removed previously. Mount fan/fixture per manufacturer's instructions.

Most of Arlington's Fan/Fixture boxes ship with an installed NM cable connector and mud cover – As well as captive installation screws for the box and bracket.

No parts to lose or misplace... they ship ready to use!



Mount Under Joist

Captive bracket installation screws

Box installation screws (use to install box UNDER joist)



1 Install FBS415/FBS420 box under the joist using the captive screws from the break-off tab.

NO LOOSE PARTS! Box and bracket installation screws ship captive, and stay in place until you're ready to use them.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Under Joist Box Depth	Unit/Std Pkg
FBS415	75204	14.6	1-1/2"	25
FBS420	75200	20.0	2"	25

Side Mount

Installed NM cable connector

NO LOOSE PARTS! Box and bracket installation screws ship captive, and stay in place until you're ready to use them.

Bracket installation screws

Use these screws to install box ON SIDE of joist

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Side Mount Box Depth	Unit/Std Pkg
FBS415S	75206	14.6	1-1/2"	25
FBS420S	75202	20.0	2"	25

1 Install FBS415S/FBS420S box on the side of the joist using the (4) captive screws removed from the break-off tab.

2 OPTION: Remove break-off tab with pliers.

3 Remove the bracket installation screws noted above. Use them to mount fan/fixture bracket to the box.

FBS415
1-1/2" deep steel box

FBS420
2" deep steel box

Arlington's octagonal steel boxes mount directly to a joist for a strong, safe fan or fixture installation. Available in two depths (1-1/2" and 2"), and two styles.

Combination hex/Phillips head screws provide easy installation with power screwdrivers.


- FBS415 and FBS420 mount securely UNDER the joist.
- UL Rated for fans/fixtures up to 70 lbs.
 - CSA Rated for 50 lb. fan or fixture

FBS415S
1-1/2" deep steel box

FBS420S
2" deep steel box

FBS415S and FBS420S mount on the SIDE of the joist.

Below installer removes captive screws in preparation for installing box to side of joist.



- UL Rated for fans/fixtures up to 70 lbs.
- CSA Rated for 50 lb. fan or fixture

Plated Steel Boxes with fully adjustable mounting brackets


FBR415

for New Construction

Arlington's super heavy-duty, plated steel fan/fixture boxes, with fully adjustable mounting brackets, are the innovative alternative to existing bar hanger brackets. Their heavy-duty construction eliminates fan wobble.

Plus, FBR415 for new construction and FBR420R, FBR407R for retrofit, ship ready to use, with all mounting hardware secured in the assembly. There are no bagged parts or pieces to lose.

- For ceilings up to 1-1/4" thick
- Mounts easily, securely between joists 16" to 24" on-center (o.c.)
- Versatile 16" to 24" o.c. positioning between joists
- 15.6 cubic inch
- UL Rated: Fans/fixtures: up to 70 lbs. at 24" o.c. up to 110 lbs. at 16" o.c.
- CSA: Fans/fixtures up to 50 lbs.
- Competitively priced!




1 "Tooth" holds bracket temporarily in place.



2 Remove screws from both ends of bracket. Use them to attach bracket to joists.




3 Adjust box position from 16" to 24" o.c. between joists.




4 Install fan mounting bracket.

Note: Drywall installation not shown



CONVENIENT. Tab positions box flush on 1/2" ceiling. Fits ceilings up to 1-1/4" thick. Bracket is scored for ease of installation.




FLEXIBLE. For flush ceiling installations on ceilings over 1/2" thick, bend the bracket along the scoreline that matches the ceiling depth.




A GREAT FINISH. FBR415 flush ceiling installation.

For Existing Construction



- 1 Cut hole in ceiling. Remove box from sled and fit mounting bracket into hole. Position bracket between joists, with bracket feet resting on the ceiling.
- 2 Tighten the hex bar with a wrench to secure bracket between joists.
- 3 Reattach box, and center it in hole. Attach bracket with screws supplied. Install fan/fixture per manufacturer's instructions.

For Wood I-Beams in Existing Construction



Arlington's FBR407R fan/fixture box is perfect for installations on wood I-beams or rafters. For a secure, UL-Rated installation there's nothing better.

Unlike other hard-to-assemble brackets, Arlington's unique slide-style bracket offers fast and easy installation. And you can position the box anywhere along the bracket for a centered installation.

FBR420R

for Existing Construction

- Mounts between joists or rafters 16" to 24" o.c.
- 20.0 cubic inch
- UL Rated: 35 lb. fans, 50 lb. fixtures
- CSA: Fans/fixtures up to 50 lbs.

FBR407R

for Wood I-Beams in Existing Construction

- Box installs flush with ceiling drywall
- For 1/2" and 5/8" thick ceilings
- No parts to lose – ships with captive box adjustment screws, fan bracket installation screws and an installed NM cable connector
- 8.0 cubic inch box
- For existing construction on wood I-beams or rafters set 16 to 24 inches on-center
- Listed to new UL standards
- UL rating 35 lb. fan • 50 lb. fixture



Fan/Fixture Box Kit for Suspended Ceilings

Designed just for mounting a fan or fixture on a suspended ceiling grid, Arlington's FBR5420SC fan/fixture box kit saves money! And 30 minutes of installation time.

The box/bracket assembly ships with the box mounted securely on-center, ready to install on a 24" grid. For a centered installation, there's no need to adjust the box or bracket, but you can position the box where you want it.

There are no parts to lose! FBR5420SC ships fully assembled. Installation and adjustment screws ship parked in place. There's an installed NM cable connector too.

- Fully adjustable mounting bracket
- 2" deep, 20.0 cubic inch box
- Meets new UL standards
- UL Rating: 70 lb fan or fixture
CSA: Acceptable for fan support
- Usable for Environmental Air Handling spaces



1 Cut a 4-1/16" diameter hole in a 24" ceiling tile.




2 Place box over hole. Place ends of support bar over the ceiling grid (tees).



3 Use the "S" hooks provided to attach chain to turnbuckle, and chain to the overhead support. Use turnbuckle to apply tension to the chain, so it supports the weight of fan.



4 Remove captive screws (shown above). Use them to install the fan or fixture per manufacturer's specifications, NEC and all local electrical codes.




Kit includes box/bracket assembly with turnbuckle, 12' heavy-duty chain, and (2) "S" hooks.

Item #	UPC/DCI/NAED MFG #01 899	Box	Description	Unit/Std Pkg
FBR5420SC	75300	2" deep 20.0 cu. in.	Fan/Fixture box kit for suspended ceilings	1/5

Fixture Box for Suspended Ceilings

UL Listed for fixtures up to 50 lbs.

Costs less than the 70 lb. rated FBR5420SC.



1 Cut a 4-1/16" diameter hole in a 24" ceiling tile.



2 Place box over hole.



3 Snap ends of support bar over the ceiling grid (tees).



4 Cable pulled through cable connector (not supplied).



5 Use FS420SCL to install fixtures, security cameras, etc. Not fan rated.

Item #	UPC/DCI/NAED MFG #01 899	Box	Description	Unit/Std Pkg
FS420SCL	12526	2" deep 20.0 cu. in.	Box for suspended ceilings, for fixtures up to 50 lbs.	1/10

One-piece, rated unit includes box, bracket and drop wire


Arlington's new all-metal box, just for fixtures, is a one-piece assembly that ships ready to install on a 24" suspended ceiling grid – No assembly required.

It's tested and rated to support exit lights, security cameras – and other light fixtures up to 50 lbs.

No more guesswork. Installers who previously attached a metal box to a bracket in the field, then added a chain or wire for support, now have an assembly that is fully tested to hold up to 50 lbs!

If the box is not perfectly positioned, loosen the appropriate screws, slide the box along the bracket and retighten the screws.

- Easy, secure mounting to ceiling grid
- Costs less than field-assembled components (box, bracket, wire)
- Saves installation time
- Usable for Environmental Air Handling spaces




For FBR5420SC and FS420SCL
OPTION: If required by local code, use sheet metal screws (not supplied) to hold bracket ends on ceiling grid.

Plastic Boxes

- FB405**
for 1/2" and 5/8" drywall
- FB407**
for 5/8" drywall
- FB412**
for 1/2" or 5/8" drywall with hat channel or furring strips, or double drywall

FB405, FB407, and FB412 offer the flexible, economical solution to 1/2" and 5/8" drywall ceiling, with or without hat channel or furring strips. FB405 and FB407 are perfect for double joists or wood I-beams.

- **Fast, easy installation**
- **Secure attachment to joist or rafter**
- **No parts to lose**
- **2-hour fire rating**
- **UL Rated: 70 lb. fans, fixtures up to 200 lbs.**
- **CSA: Fans/fixtures up to 50 lbs.**



Box Installation



1 The FB412 fan/fixture box is perfect for 1/2" or 5/8" drywall with 3/4" furring strips or hat channel with a single layer of drywall...



2 ...or double drywall (shown as cutaway).

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Drywall Thickness	Unit/Std Pkg
FB405	72185	6.0	1/2" or 5/8"	25
FB407	72177	8.0	5/8"	25
FB412	72189	14.5	1/2" or 5/8" *	25

* w/ furring strips or hat channel with a single layer of drywall or with a double layer of drywall

Plastic Boxes - Press Hold • Joist Mount


- FB415**
for 1/2" and 5/8" drywall
- FB426**
for 1/2" and 5/8" drywall
- FB423**
for 1/2" or 5/8" drywall with hat channel or furring strips with a single layer of drywall, or double drywall

FB415 and FB426 come with the screws you need to install the box and bracket, held captive until you're ready to use them.

Press Hold...Speed, Convenience, Safety

These boxes have gripping tangs that press-hold the box to the joist while you reach for your screwdriver. Tightening the center screw affixes the box onto the joist for a super-secure installation.

- **2-hour fire rating**
- **UL Rated: 70 lb. fans, fixtures up to 200 lbs.**
- **CSA: Fans/fixtures up to 50 lbs.**



Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Drywall Thickness	Unit/Std Pkg
FB415	72167	10.3	1/2" or 5/8"	25
FB426	72179	16.0	1/2" or 5/8"	25
FB426F	12521	16.0	1/2" or 5/8"	25
FB423	72190	19.5	1/2" or 5/8" *	25

* w/ furring strips or hat channel with a single layer of drywall or with a double layer of drywall




NEW! Flanged design forms a protective barrier against air infiltration.



1 Convenient. Gripping tangs hold box in place temporarily, until the center screw is tightened.



2 Push NM sheathed cable through connector.



3 Remove (2) long parked screws. Use them to install bracket.



4 The fan/fixture bracket installs directly onto the joist through the oval slots in the box.



5 Cable pulled through installed NM cable connector.

All of Arlington's Fan/Fixture boxes ship with an installed NM cable connector and mud cover – as well as captive installation screws for the box and bracket.

No parts to lose or misplace...ready to use!



Plastic Boxes

FB444
Our largest capacity
L-shaped box


FB442
FB443
Lowest cost L-shaped boxes

FB444 is the largest capacity box we make! Its 25.6 cubic inch capacity provides plenty of room for wires – easy access too!

The slightly smaller FB443 and FB442 offer the same great features and benefits at a lower cost.

- Boxes mount to single or double joists or rafters with a shipped-in-place center screw
- Locator posts assure correct positioning of bracket
- UL Rated: 70 lb. fans, fixtures up to 200 lbs.
- CSA: Fans/fixtures up to 50 lbs.
- 2-hour fire rating





Locator Post

FB442

Locator Post for bracket installation screws

FB444

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Drywall Thickness	Unit/Std Pkg
FB442	72194	13.4	1/2" or 5/8"	25
FB443	72197	17.96	1/2" or 5/8"	25
FB444	72187	25.6	1/2" or 5/8"	25

FB442 Installation




1 Secure! Side mount the box to the joist using the shipped-in-place center screw.

2 Pull wires. (Drywall installation omitted) After ceiling is installed, remove captive installation screws – use them to install bracket.

3 Done! Install fan or fixture per manufacturer's instructions.

FB444 Installation



1 Fast and easy installation on single or double joists!

2 Accurate! Locator posts on these L-shaped boxes assure proper positioning of the installation bracket.




3 Easy. Bracket installation on FB444. (Drywall installation not shown)

4 Easy access. FB444 OPTION: To restuff wires, open bottom of the box – before drywall installation.


Plastic Boxes with Steel Bracket

Nail On Attachment to Single or Double Joists



FB417S

FB417SLP



Single Joist

Double Joist

FB417S

FB417S

Fast. Simply nail the box to the joist. Indicator lines on FB417S assure proper positioning on the joist for the ceiling thickness.

FB417S and FB417SLP side mount to single or double joists for a super-secure installation.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Ceiling Thickness	Unit/Std Pkg
FB417S	72177	20.0	up to 1-1/2"	25
FB417SLP *	72199	20.0	1/2" or 5/8"	25

* Also works on manufactured I-beams

Most of Arlington's Fan/Fixture boxes ship with an installed NM cable connector and mud cover – As well as captive installation screws for the box and bracket.

No parts to lose or misplace... ready to use!

FB417S
for ceilings
up to 1-1/2" thick,
including single-sheeted
drywall mounted to furring
strips or hat channel –
or double drywall

FB417SLP
Low profile for
1/2" or 5/8" ceilings

FB417S saves time! Nail on installation, and indicator marks for 1/2", 5/8", and 3/4" ceiling thicknesses make it the logical choice for speedy attachment to single or double joists.

For added convenience, use the low profile FB417SLP for 1/2" or 5/8" ceilings. Also works for manufactured I-beams.

Both ship ready to use, with the nail in place and captive bracket installation screws.

- No loose parts – totally self-contained
- Combination hex/Phillips head screws for easy installation with power screwdrivers
- Nail on installation
- 20.0 cubic inch
- 2-hour fire rating
- UL Rated: Fans/fixtures up to 70 lbs.
- CSA: Fans/fixtures up to 50 lbs.

8" Mounting Block with built-in box for fan and fixture installations

Fan/Fixture Boxes

- MB8
- 6.1 Cubic inches
- Ceiling medallion and electrical box combined
 - Supports flood lights, smoke detectors, fans, light fixtures – any fixture needing a safe, strong installation.
 - UV rated plastic
 - For interior or exterior use
 - Mounts directly to soffit or ceiling joist without the need to cut ceiling drywall
 - Paintable
 - UL Rated: 70 lb. fan, 200 lb. fixture; CSA rated: 50 lb. fan/fixture


Canadian orders ship with grounding lug required by CSA for use with fixtures.



MB8 includes... Two #10 x 3" wood screws, one #8 x 1-1/2" wood screw, two KOs, and one NM94 non-metallic cable connector.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Use and Box Depth	Unit/Std Pkg
MB8	42330	6.1	Flat Mount	1/10

MB8 Installation



1 Locate the ceiling joist using a stud finder or similar device. Drill a hole approximately 1/2" in diameter, in the ceiling next to the joist. Remove desired knockout. Insert the cable connector into the opening. Pull the NM cable through the connector.




2 Using the #8 x 1-1/2" wood screws provided, mount the MB8 to the joist (through the ceiling).



3 Install the fixture or fan mounting bar (provided with the fixture or fan) directly to the joist with the (2) #10 x 3" wood screws and lock washers provided. Wire the fixture or fan following the instructions included with the product.

Steel Box – Side Mounts to Joist NEW!

- FBS1423
- 23.0 Cubic inches
- Designed for new construction or retrofit, this deep steel box side mounts to a joist for a super secure, fan-rated installation.
- UL Rated for fans/fixtures up to 70 lbs.
 - CSA: Fans/fixtures up to 50 lbs.



Place box at proper depth; attach to joist with three captive screws in the box.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Side Mount Box Depth	Unit/Std Pkg
FBS1423	76190	23.0	2.375"	10



Fan/Fixture Box Rating and # of Single Conductors									
Catalog Number	Category	Cubic Inches (Lbs.)	UL Fan Load Rating (Lbs.)	CSA Fan Load Rating (Lbs.)	UL Fixture Static Rating (Lbs.)	CSA Fixture Static Rating	# Of Single Conductors		
							#14 or	#12 or	#10
FB405	PLASTIC	6.0	70	50	200	50	3	—	—
FB4050	PLASTIC	6.0	70	50	200	50	3	—	—
FB407	PLASTIC	8.0	70	50	200	50	4	3	3
FB4070	PLASTIC	8.0	70	50	200	50	4	3	3
FB412	PLASTIC	14.4	70	50	200	50	7	6	5
FB415	PLASTIC	10.3	70	50	200	50	5	4	4
FB4150	PLASTIC	10.3	70	50	200	50	5	4	4
FB417S	PLASTIC & STEEL	20.0	70	50	70	50	10	8	8
FB417SLP	PLASTIC & STEEL	20.0	70	50	70	50	10	8	8
FB423	PLASTIC	19.5	70	50	200	50	9	8	7
FB426	PLASTIC	16.0	70	50	200	50	8	7	6
FB426F	PLASTIC	16.0	70	50	200	50	8	7	6
FB442	PLASTIC	13.4	70	50	200	50	6	4	4
FB443	PLASTIC	17.96	70	50	200	50	8	7	7
FB444	PLASTIC	25.6	70	50	200	50	13	11	10
FB450	PLASTIC	14.5	70	50	200	50	7	6	5
FB900	PLASTIC	14.5	70	50	200	50	7	6	5
FBRS407R	STEEL	8.0	35	50	50	50	4	3	3
FBRS415	STEEL	15.6	70 @ 24" o.c. 110 @ 16" o.c.	50	70 @ 24" o.c. 110 @ 16" o.c.	50	7	6	6
FBRS420R	STEEL	20.0	35	50	50	50	10	8	8
FBRS420SC	STEEL	20.0	35	50	50	50	10	8	8
FBS1423	STEEL	23.0	70	50	70	50	11	10	9
FBS405	STEEL	6.0	70	50	200	50	3	—	—
FBS405T	STEEL	6.0	70	50	200	50	3	—	—
FBS407	STEEL	8.0	70	50	200	50	4	3	3
FBS407T	STEEL	8.0	70	50	200	50	4	3	3
FBS415	STEEL	14.6	70	50	200	50	7	6	6
FBS415S	STEEL	14.6	70	50	70	50	7	6	6
FBS420	STEEL	20.0	70	50	200	50	10	8	8
FBS420S	STEEL	20.0	70	50	70	50	10	8	8
FBX900	PLASTIC & STEEL	14.5	70	50	70	50	7	6	5
FS420SCL	STEEL	20.0	—	—	25	25	10	8	8
MB8	PLASTIC	6.1	70	50	200	50	3	—	—

Most of of Arlington's Fan/Fixture boxes ship with an installed NM cable connector and mud cover – As well as captive installation screws for the box and bracket.
No parts to lose or misplace...ready to use!




SAVE MONEY!

FAN/FIXTURE BOX just for SUSPENDED CEILINGS



Save 30 minutes of assembly time with Arlington's new fan/fixture box. It ships with the box and bracket assembly mounted on center, ready to install on a 24" suspended ceiling grid.

- No parts to lose
- Installation and adjustment screws ship captive
- 2" deep, 20.0 cu. inch box




FLUSH WITH CEILING

FAN/FIXTURE BOX with ADJUSTABLE BRACKET



Arlington's heavy-duty, plated steel fan/fixture box has an adjustable bracket that fits 16" to 24" o.c.


Flush ceiling installations!
FBR5415 is designed for ceilings up to 1-1/4" thick. For 1/2" ceilings, use the pre-bent positioning tab.



FIXTURE BOX

TESTED WEIGHT RATING LISTED AS 1-PIECE UNIT

for SUSPENDED CEILINGS



Arlington's new all-metal, one-piece fixture box ships ready to install on a 24" suspended ceiling grid. There's no assembly required!

It's tested and rated to support exit lights, security cameras and other light fixtures up to 50 lbs.

No more guesswork. Installers who attached a metal box to a bracket in the field, then added a chain or wire for support, now have an assembly that's *fully tested* to hold up to 50 lbs!

FS420SCL is UL/CSA Listed as a complete unit: box, bracket, drop wire.

- Box can be positioned anywhere along bracket
- Costs less than field-assembled components (box, bracket, wire)
- Usable for Environmental Air Handling spaces

Distributed by



Arlington

1 Stauffer Industrial Park
Scranton, PA 18517
800/233.4717
Fax 570/562.0646
www.aifittings.com

©2008 Arlington Industries, Inc.

Arlington's fan/fixture boxes are patented (or other patents pending).



FAN & FIXTURE BOXES

FOR A VARIETY OF USES




Choose the Fan or Fixture Box that's right for you...


...in Steel or Plastic – or a Combination!

No matter what your needs – or installation preferences, Arlington has a fan/fixture box to fit.

We manufacture a variety of steel and non-metallic boxes in many depths and cubic inch capacities that install directly to the joist(s) for an extra-secure installation.



Our boxes that mount to the bottom of a joist deliver a safe, secure installation because both the box and the bracket install directly to the joist!



Plus, we have a box for every ceiling condition!


Joist Mount

page 4

FBS405, FBS405T
6.0 cubic inches
FBS407, FBS407T
8.0 cubic inches



for NEW CONSTRUCTION



Joist Mount

page 10

FB405
6.0 cubic inches
FB407
8.0 cubic inches
FB412
14.4 cubic inches



Plastic

Each of our boxes is UL Listed to hold fans and fixtures of a specific weight; generally from 35 to 200 lbs., depending on the box. In addition, our non-metallic boxes offer a 2-hour fire rating.



Under-Joist Mount

page 5

FBS415
1-1/2" depth
14.6 cubic inches
FBS420
2" depth
20.0 cubic inches



For NEW CONSTRUCTION



Press Hold Joist Mount

page 11

FB415
10.3 cubic inches
FB423
19.5 cubic inches
FB426
16.0 cubic inches



For ceilings up to 1-1/2" thick.

Applications include:

- 1/2" or 5/8" drywall
- Double drywall
- Drywall mounted to hat channel, or furring strips, then to the joist
- Single or double joists



Side Mount

page 5

FBS415S
1-1/2" depth
14.6 cubic inches
FBS420S
2" depth
20.0 cubic inches



For NEW CONSTRUCTION



Side Mount

page 12


FB442
13.4 cubic inches
FB443
17.96 cubic inches
FB444
25.6 cubic inches



Mounts Between Joists Adjustable Brackets

pages 6-7

FBR415
15.6 cubic inches
FBR407R
8.0 cubic inches
FBR420R
2" depth
20.0 cubic inches



For NEW CONSTRUCTION

For RETROFIT



Side Mount Plastic Box with Steel Bracket

page 13

FB417S
20.0 cubic inches
Low profile
FB417SLP
20.0 cubic inches



Steel & Plastic

Most of Arlington's fan boxes ship with an installed NM cable connector, mud cover in place and captive installation screws for both the box and the fan/fixture mounting bracket.



For Any Suspended Ceiling Frame

page 8

FBR420SC, FS420SCL
2" depth
20.0 cubic inches

Steel



8" Mounting Block

page 14

MB8
6.1 cubic inches



Arlington's fan/fixture boxes are patented (or other patents pending).



FBS405
for 1/2" and 5/8" drywall

FBS407
for 5/8" drywall

Designed for 1/2" or 5/8" drywall ceilings, our cost-effective, plated steel FBS405 and FBS407 pan boxes mount directly to a ceiling joist for a super-secure installation.

- For NEW CONSTRUCTION
- UL Rated for 70 lb. fans; 200 lb. fixtures
- CSA Rated for 50 lb. fan or fixture

Protective plastic tips

Installed mud cover

Captive installation screws remain in place until used

Installed NM cable connector

Green ground screw

FBS405T
inside view

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Ceiling Thickness	Unit/Std Pkg
FBS405	76185	6.0	1/2", 5/8"	25
FBS407	76187	8.0	5/8"	25
*FBS405T	40500	6.0	1/2", 5/8"	25
*FBS407T	40700	8.0	5/8"	25

* with threaded openings and #10 screws (supplied) for mounting fan/fixture bracket.

1 Secure installation! Box mounts directly to joist with captive screw near center.

2 Convenient. Drill (2) 1/8" dia. holes into joist through elongated openings on each side of box. Remove the (2) screws noted above. Use to mount the bracket...

3 Easy. Mount bracket into the holes with the (2) long screws removed previously. Mount fan/fixture per manufacturer's instructions.

Most of Arlington's Fan/Fixture boxes ship with an installed NM cable connector and mud cover – As well as captive installation screws for the box and bracket.

No parts to lose or misplace... they ship ready to use!



Mount Under Joist

Captive bracket installation screws

Box installation screws (use to install box UNDER joist)



1 Install FBS415/FBS420 box under the joist using the captive screws from the break-off tab.

NO LOOSE PARTS! Box and bracket installation screws ship captive, and stay in place until you're ready to use them.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Under Joist Box Depth	Unit/Std Pkg
FBS415	75204	14.6	1-1/2"	25
FBS420	75200	20.0	2"	25

Side Mount

Installed NM cable connector

NO LOOSE PARTS! Box and bracket installation screws ship captive, and stay in place until you're ready to use them.

Bracket installation screws

Use these screws to install box ON SIDE of joist

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Side Mount Box Depth	Unit/Std Pkg
FBS415S	75206	14.6	1-1/2"	25
FBS420S	75202	20.0	2"	25

1 Install FBS415S/FBS420S box on the side of the joist using the (4) captive screws removed from the break-off tab.

2 OPTION: Remove break-off tab with pliers.

3 Remove the bracket installation screws noted above. Use them to mount fan/fixture bracket to the box.

FBS415
1-1/2" deep steel box

FBS420
2" deep steel box

Arlington's octagonal steel boxes mount directly to a joist for a strong, safe fan or fixture installation. Available in two depths (1-1/2" and 2"), and two styles.

Combination hex/Phillips head screws provide easy installation with power screwdrivers.

- FBS415 and FBS420 mount securely UNDER the joist.
- UL Rated for fans/fixtures up to 70 lbs.
 - CSA Rated for 50 lb. fan or fixture

FBS415S
1-1/2" deep steel box

FBS420S
2" deep steel box

FBS415S and FBS420S mount on the SIDE of the joist.

Below installer removes captive screws in preparation for installing box to side of joist.

-
- UL Rated for fans/fixtures up to 70 lbs.
 - CSA Rated for 50 lb. fan or fixture

Plated Steel Boxes with fully adjustable mounting brackets

FBR415

for New Construction

Arlington's super heavy-duty, plated steel fan/fixture boxes, with fully adjustable mounting brackets, are the innovative alternative to existing bar hanger brackets. Their heavy-duty construction eliminates fan wobble.

Plus, FBR415 for new construction and FBR420R, FBR407R for retrofit, ship ready to use, with all mounting hardware secured in the assembly. There are no bagged parts or pieces to lose.

- For ceilings up to 1-1/4" thick
- Mounts easily, securely between joists 16" to 24" on-center (o.c.)
- Versatile 16" to 24" o.c. positioning between joists
- 15.6 cubic inch
- UL Rated: Fans/fixtures: up to 70 lbs. at 24" o.c. up to 110 lbs. at 16" o.c.
- CSA: Fans/fixtures up to 50 lbs.
- Competitively priced!

For New Construction

1. Adjust box position between joists with this screw.

2. Locator tab is pre-set to position box properly on 1/2" ceiling thickness.

3. Adjust box position between joists with this screw.

4. Adjust box position between joists with this screw.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Use and Box Depth	Unit/Std Pkg
FBR415	72250	15.6	New Construction	1/10 Ceilings up to 1-1/4"




1 "Tooth" holds bracket temporarily in place.



2 Remove screws from both ends of bracket. Use them to attach bracket to joists.




3 Adjust box position from 16" to 24" o.c. between joists.




4 Install fan mounting bracket.

Note: Drywall installation not shown



CONVENIENT. Tab positions box flush on 1/2" ceiling. Fits ceilings up to 1-1/4" thick. Bracket is scored for ease of installation.



FLEXIBLE. For flush ceiling installations on ceilings over 1/2" thick, bend the bracket along the scoreline that matches the ceiling depth.



A GREAT FINISH. FBR415 flush ceiling installation.

Plated Steel Boxes with fully adjustable mounting brackets

FBR420R

for Existing Construction

- Mounts between joists or rafters 16" to 24" o.c.
- 20.0 cubic inch
- UL Rated: 35 lb. fans, 50 lb. fixtures
- CSA: Fans/fixtures up to 50 lbs.

For Existing Construction

1. Cut hole in ceiling. Remove box from sled and fit mounting bracket into hole. Position bracket between joists, with bracket feet resting on the ceiling.

2. Tighten the hex bar with a wrench to secure bracket between joists.

3. Reattach box, and center it in hole. Attach bracket with screws supplied. Install fan/fixture per manufacturer's instructions.

As the hex bar is tightened, bracket ends bite into the joists, holding the unit secure.

Remove, and use these captive screws to install fan/fixture bracket.

Sled

Bracket feet

FBR420R

For Wood I-Beams in Existing Construction

1. Unique slide-style bracket

2. Drywall cut away to show installation between I-beams

3. FBR407R

Arlington's FBR407R fan/fixture box is perfect for installations on wood I-beams or rafters. For a secure, UL-Rated installation there's nothing better.

Unlike other hard-to-assemble brackets, Arlington's unique slide-style bracket offers fast and easy installation. And you can position the box anywhere along the bracket for a centered installation.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Use and Box Depth	Unit/Std Pkg
FBR420R	75325	20.0	Retrofit 2" Box	1/10
FBR407R	72248	8.0	Retrofit on Wood I-beams	1/10

FBR407R

for Wood I-Beams in Existing Construction

- Box installs flush with ceiling drywall
- For 1/2" and 5/8" thick ceilings
- No parts to lose – ships with captive box adjustment screws, fan bracket installation screws and an installed NM cable connector
- 8.0 cubic inch box
- For existing construction on wood I-beams or rafters set 16 to 24 inches on-center
- Listed to new UL standards
- UL rating 35 lb. fan • 50 lb. fixture



Fan/Fixture Box Kit for Suspended Ceilings

Designed just for mounting a fan or fixture on a suspended ceiling grid, Arlington's FBR5420SC fan/fixture box kit saves money! And 30 minutes of installation time.

The box/bracket assembly ships with the box mounted securely on-center, ready to install on a 24" grid. For a centered installation, there's no need to adjust the box or bracket, but you can position the box where you want it.

There are no parts to lose! FBR5420SC ships fully assembled. Installation and adjustment screws ship parked in place. There's an installed NM cable connector too.

- Fully adjustable mounting bracket
- 2" deep, 20.0 cubic inch box
- Meets new UL standards
- UL Rating: 70 lb fan or fixture
CSA: Acceptable for fan support
- Usable for Environmental Air Handling spaces



1 Cut a 4-1/16" diameter hole in a 24" ceiling tile.




2 Place box over hole. Place ends of support bar over the ceiling grid (tees).



3 Use the "S" hooks provided to attach chain to turnbuckle, and chain to the overhead support. Use turnbuckle to apply tension to the chain, so it supports the weight of fan.



4 Remove captive screws (shown above). Use them to install the fan or fixture per manufacturer's specifications, NEC and all local electrical codes.




Kit includes box/bracket assembly with turnbuckle, 12' heavy-duty chain, and (2) "S" hooks.

Item #	UPC/DCI/NAED MFG #01 899	Box	Description	Unit/Std Pkg
FBR5420SC	75300	2" deep 20.0 cu. in.	Fan/Fixture box kit for suspended ceilings	1/5

Fixture Box for Suspended Ceilings

UL Listed for fixtures up to 50 lbs.

Costs less than the 70 lb. rated FBR5420SC.



1 Cut a 4-1/16" diameter hole in a 24" ceiling tile.



2 Place box over hole.



3 Snap ends of support bar over the ceiling grid (tees).



4 Cable pulled through cable connector (not supplied).



5 Use FS420SCL to install fixtures, security cameras, etc. Not fan rated.

Item #	UPC/DCI/NAED MFG #01 899	Box	Description	Unit/Std Pkg
FS420SCL	12526	2" deep 20.0 cu. in.	Box for suspended ceilings, for fixtures up to 50 lbs.	1/10

One-piece, rated unit includes box, bracket and drop wire


Arlington's new all-metal box, just for fixtures, is a one-piece assembly that ships ready to install on a 24" suspended ceiling grid – No assembly required.

It's tested and rated to support exit lights, security cameras – and other light fixtures up to 50 lbs.

No more guesswork. Installers who previously attached a metal box to a bracket in the field, then added a chain or wire for support, now have an assembly that is fully tested to hold up to 50 lbs!

If the box is not perfectly positioned, loosen the appropriate screws, slide the box along the bracket and retighten the screws.

- Easy, secure mounting to ceiling grid
- Costs less than field-assembled components (box, bracket, wire)
- Saves installation time
- Usable for Environmental Air Handling spaces




For FBR5420SC and FS420SCL
OPTION: If required by local code, use sheet metal screws (not supplied) to hold bracket ends on ceiling grid.

Plastic Boxes

- FB405**
for 1/2" and 5/8" drywall
- FB407**
for 5/8" drywall
- FB412**
for 1/2" or 5/8" drywall with hat channel or furring strips, or double drywall

FB405, FB407, and FB412 offer the flexible, economical solution to 1/2" and 5/8" drywall ceiling, with or without hat channel or furring strips. FB405 and FB407 are perfect for double joists or wood I-beams.

- **Fast, easy installation**
- **Secure attachment to joist or rafter**
- **No parts to lose**
- **2-hour fire rating**
- **UL Rated: 70 lb. fans, fixtures up to 200 lbs.**
- **CSA: Fans/fixtures up to 50 lbs.**



Box Installation



1 The FB412 fan/fixture box is perfect for 1/2" or 5/8" drywall with 3/4" furring strips or hat channel with a single layer of drywall...



2 ...or double drywall (shown as cutaway).

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Drywall Thickness	Unit/Std Pkg
FB405	72185	6.0	1/2" or 5/8"	25
FB407	72177	8.0	5/8"	25
FB412	72189	14.5	1/2" or 5/8" *	25

* w/ furring strips or hat channel with a single layer of drywall or with a double layer of drywall



Plastic Boxes - Press Hold • Joist Mount


- FB415**
for 1/2" and 5/8" drywall
- FB426**
for 1/2" and 5/8" drywall
- FB423**
for 1/2" or 5/8" drywall with hat channel or furring strips with a single layer of drywall, or double drywall

FB415 and FB426 come with the screws you need to install the box and bracket, held captive until you're ready to use them.

Press Hold...Speed, Convenience, Safety

These boxes have gripping tangs that press-hold the box to the joist while you reach for your screwdriver. Tightening the center screw affixes the box onto the joist for a super-secure installation.

- **2-hour fire rating**
- **UL Rated: 70 lb. fans, fixtures up to 200 lbs.**
- **CSA: Fans/fixtures up to 50 lbs.**



Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Drywall Thickness	Unit/Std Pkg
FB415	72167	10.3	1/2" or 5/8"	25
FB426	72179	16.0	1/2" or 5/8"	25
FB426F	12521	16.0	1/2" or 5/8"	25
FB423	72190	19.5	1/2" or 5/8" *	25

* w/ furring strips or hat channel with a single layer of drywall or with a double layer of drywall




NEW! Flanged design forms a protective barrier against air infiltration.



1 Convenient. Gripping tangs hold box in place temporarily, until the center screw is tightened.



2 Push NM sheathed cable through connector.



3 Remove (2) long parked screws. Use them to install bracket.



4 The fan/fixture bracket installs directly onto the joist through the oval slots in the box.



5 Cable pulled through installed NM cable connector.

All of Arlington's Fan/Fixture boxes ship with an installed NM cable connector and mud cover – as well as captive installation screws for the box and bracket.

No parts to lose or misplace...ready to use!



Plastic Boxes

FB444
Our largest capacity
L-shaped box


FB442
FB443
Lowest cost L-shaped boxes

FB444 is the largest capacity box we make! Its 25.6 cubic inch capacity provides plenty of room for wires – easy access too!

The slightly smaller FB443 and FB442 offer the same great features and benefits at a lower cost.

- Boxes mount to single or double joists or rafters with a shipped-in-place center screw
- Locator posts assure correct positioning of bracket
- UL Rated: 70 lb. fans, fixtures up to 200 lbs.
- CSA: Fans/fixtures up to 50 lbs.
- 2-hour fire rating





Locator Post

FB442

Locator Post for bracket installation screws

FB444

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Drywall Thickness	Unit/Std Pkg
FB442	72194	13.4	1/2" or 5/8"	25
FB443	72197	17.96	1/2" or 5/8"	25
FB444	72187	25.6	1/2" or 5/8"	25

FB442 Installation




1 Secure! Side mount the box to the joist using the shipped-in-place center screw.

2 Pull wires. (Drywall installation omitted) After ceiling is installed, remove captive installation screws – use them to install bracket.

3 Done! Install fan or fixture per manufacturer's instructions.

FB444 Installation



1 Fast and easy installation on single or double joists!

2 Accurate! Locator posts on these L-shaped boxes assure proper positioning of the installation bracket.




3 Easy. Bracket installation on FB444. (Drywall installation not shown)

4 Easy access. FB444 OPTION: To restuff wires, open bottom of the box – before drywall installation.


Plastic Boxes with Steel Bracket

Nail On Attachment to Single or Double Joists



FB417S

FB417SLP



Single Joist

Double Joist

FB417S

FB417S

Fast. Simply nail the box to the joist. Indicator lines on FB417S assure proper positioning on the joist for the ceiling thickness.

FB417S and FB417SLP side mount to single or double joists for a super-secure installation.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Ceiling Thickness	Unit/Std Pkg
FB417S	72177	20.0	up to 1-1/2"	25
FB417SLP *	72199	20.0	1/2" or 5/8"	25

* Also works on manufactured I-beams

Most of Arlington's Fan/Fixture boxes ship with an installed NM cable connector and mud cover – As well as captive installation screws for the box and bracket.

No parts to lose or misplace... ready to use!

FB417S
for ceilings
up to 1-1/2" thick,
including single-sheeted
drywall mounted to furring
strips or hat channel –
or double drywall

FB417SLP
Low profile for
1/2" or 5/8" ceilings

FB417S saves time! Nail on installation, and indicator marks for 1/2", 5/8", and 3/4" ceiling thicknesses make it the logical choice for speedy attachment to single or double joists.

For added convenience, use the low profile FB417SLP for 1/2" or 5/8" ceilings. Also works for manufactured I-beams.

Both ship ready to use, with the nail in place and captive bracket installation screws.

- No loose parts – totally self-contained
- Combination hex/Phillips head screws for easy installation with power screwdrivers
- Nail on installation
- 20.0 cubic inch
- 2-hour fire rating
- UL Rated: Fans/fixtures up to 70 lbs.
- CSA: Fans/fixtures up to 50 lbs.

- MB8
- 6.1 Cubic inches
- Ceiling medallion and electrical box combined
 - Supports flood lights, smoke detectors, fans, light fixtures – any fixture needing a safe, strong installation.
 - UV rated plastic
 - For interior or exterior use
 - Mounts directly to soffit or ceiling joist without the need to cut ceiling drywall
 - Paintable
 - UL Rated: 70 lb. fan, 200 lb. fixture; CSA rated: 50 lb. fan/fixture


Canadian orders ship with grounding lug required by CSA for use with fixtures.



MB8 includes...
Two #10 x 3" wood screws, one #8 x 1-1/2" wood screw, two KOs, and one NM94 non-metallic cable connector.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Use and Box Depth	Unit/Std Pkg
MB8	42330	6.1	Flat Mount	1/10

MB8 Installation



1 Locate the ceiling joist using a stud finder or similar device. Drill a hole approximately 1/2" in diameter, in the ceiling next to the joist. Remove desired knockout. Insert the cable connector into the opening. Pull the NM cable through the connector.



2 Using the #8 x 1-1/2" wood screws provided, mount the MB8 to the joist (through the ceiling).




3 Install the fixture or fan mounting bar (provided with the fixture or fan) directly to the joist with the (2) #10 x 3" wood screws and lock washers provided. Wire the fixture or fan following the instructions included with the product.

Steel Box – Side Mounts to Joist NEW!

- FBS1423
- 23.0 Cubic inches
- Designed for new construction or retrofit, this deep steel box side mounts to a joist for a super secure, fan-rated installation.

 - UL Rated for fans/fixtures up to 70 lbs.
 - CSA: Fans/fixtures up to 50 lbs.



Place box at proper depth; attach to joist with three captive screws in the box.

Item #	UPC/DCI/NAED MFG #01 899	Cubic Inches	Side Mount Box Depth	Unit/Std Pkg
FBS1423	76190	23.0	2.375"	10



Fan/Fixture Box Rating and # of Single Conductors									
Catalog Number	Category	Cubic Inches (Lbs.)	UL Fan Load Rating (Lbs.)	CSA Fan Load Rating (Lbs.)	UL Fixture Static Rating (Lbs.)	CSA Fixture Static Rating	# Of Single Conductors		
							#14 or	#12 or	#10
FB405	PLASTIC	6.0	70	50	200	50	3	—	—
FB4050	PLASTIC	6.0	70	50	200	50	3	—	—
FB407	PLASTIC	8.0	70	50	200	50	4	3	3
FB4070	PLASTIC	8.0	70	50	200	50	4	3	3
FB412	PLASTIC	14.4	70	50	200	50	7	6	5
FB415	PLASTIC	10.3	70	50	200	50	5	4	4
FB4150	PLASTIC	10.3	70	50	200	50	5	4	4
FB417S	PLASTIC & STEEL	20.0	70	50	70	50	10	8	8
FB417SLP	PLASTIC & STEEL	20.0	70	50	70	50	10	8	8
FB423	PLASTIC	19.5	70	50	200	50	9	8	7
FB426	PLASTIC	16.0	70	50	200	50	8	7	6
FB426F	PLASTIC	16.0	70	50	200	50	8	7	6
FB442	PLASTIC	13.4	70	50	200	50	6	4	4
FB443	PLASTIC	17.96	70	50	200	50	8	7	7
FB444	PLASTIC	25.6	70	50	200	50	13	11	10
FB450	PLASTIC	14.5	70	50	200	50	7	6	5
FB900	PLASTIC	14.5	70	50	200	50	7	6	5
FBRS407R	STEEL	8.0	35	50	50	50	4	3	3
FBRS415	STEEL	15.6	70 @ 24" o.c. 110 @ 16" o.c.	50	70 @ 24" o.c. 110 @ 16" o.c.	50	7	6	6
FBRS420R	STEEL	20.0	35	50	50	50	10	8	8
FBRS420SC	STEEL	20.0	35	50	50	50	10	8	8
FBS1423	STEEL	23.0	70	50	70	50	11	10	9
FBS405	STEEL	6.0	70	50	200	50	3	—	—
FBS405T	STEEL	6.0	70	50	200	50	3	—	—
FBS407	STEEL	8.0	70	50	200	50	4	3	3
FBS407T	STEEL	8.0	70	50	200	50	4	3	3
FBS415	STEEL	14.6	70	50	200	50	7	6	6
FBS415S	STEEL	14.6	70	50	70	50	7	6	6
FBS420	STEEL	20.0	70	50	200	50	10	8	8
FBS420S	STEEL	20.0	70	50	70	50	10	8	8
FBX900	PLASTIC & STEEL	14.5	70	50	70	50	7	6	5
FS420SCL	STEEL	20.0	—	—	25	25	10	8	8
MB8	PLASTIC	6.1	70	50	200	50	3	—	—

Most of of Arlington's Fan/Fixture boxes ship with an installed NM cable connector and mud cover – As well as captive installation screws for the box and bracket.
No parts to lose or misplace...ready to use!




SAVE MONEY!

FAN/FIXTURE BOX just for SUSPENDED CEILINGS



Save 30 minutes of assembly time with Arlington's new fan/fixture box. It ships with the box and bracket assembly mounted on center, ready to install on a 24" suspended ceiling grid.

- No parts to lose
- Installation and adjustment screws ship captive
- 2" deep, 20.0 cu. inch box




FLUSH WITH CEILING

FAN/FIXTURE BOX with ADJUSTABLE BRACKET



Arlington's heavy-duty, plated steel fan/fixture box has an adjustable bracket that fits 16" to 24" o.c.

Flush ceiling installations!
FBR5415 is designed for ceilings up to 1-1/4" thick. For 1/2" ceilings, use the pre-bent positioning tab.



For other ceiling thicknesses, bend along the appropriate score line.

- 15.6 cu. inch box
- Ships with captive screws, mud cover, installed NM cable connector



FIXTURE BOX

TESTED WEIGHT RATING LISTED AS 1-PIECE UNIT

for SUSPENDED CEILINGS



Arlington's new all-metal, one-piece fixture box ships ready to install on a 24" suspended ceiling grid. There's no assembly required!

It's tested and rated to support exit lights, security cameras and other light fixtures up to 50 lbs.

No more guesswork. Installers who attached a metal box to a bracket in the field, then added a chain or wire for support, now have an assembly that's *fully tested* to hold up to 50 lbs!

FS420SCL is UL/CSA Listed as a complete unit: box, bracket, drop wire.

- Box can be positioned anywhere along bracket
- Costs less than field-assembled components (box, bracket, wire)
- Usable for Environmental Air Handling spaces

Distributed by

A  
Arlington

1 Stauffer Industrial Park
Scranton, PA 18517
800/233.4717
Fax 570/562.0646
www.aifittings.com

©2008 Arlington Industries, Inc.

Arlington's fan/fixture boxes are patented (or other patents pending).