

ELLIOTT ELECTRIC SUPPLY 2501 Cavitt Avenue 77801-0000, TX Bryan Phone: 979-779-6630 Fax: 979-779-6620



FD2SA Alu FD Box

Crouse-Hinds

Catalog Number	FD2SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FD Device Box, Deep, Copper-Free Aluminum, Single-Gang, 3/4"
Weight per unit	1.1 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

Features

Cable Entry	(1) End
dimensions	5.1600 IN X 2.6900 IN X 2.7500 IN
Material	Natural Finished Sand Copper Free Aluminum

Dimensions and Weight

Sizo	2/4 in
SIZE	3/4 111

ALU FD BOX

Descriptions

Description

Description	NEC 1 D DOX
extra long description	CRS-H FD2 SA 3/4 NPT DE AL FD BX SG
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FD device box, Deep, Copper-free aluminum, Single-gang, 3/4"
Product Type	3/4 NPT De AI FD BX SGL GNG MTG Lugs
Special Features	Configuration Type FD, Dimension 2-3/4 In Width X 2-11/16 In Depth X 5-5/32 In Height

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274745091
Manufacturers Part Number	FD2 SA
UPC	782274745091

Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2501 Cavitt Avenue 77801-0000, TX Bryan Phone: 979-779-6630 Fax: 979-779-6620

Packaging	
Carton	1
Package	2
Weight Per each	1.08
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	FLUSH

UL 514, CSA C22.2, Federal Specification W-C-5860