



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

217 Innovation Way  
37075-0000, TN Hendersonville  
Phone: 615-991-2399  
Fax: 000-000-0000



## FDC2 3/4" 1G Dev Box *Crouse-Hinds*

Catalog Number	FDC2
Manufacturer	Crouse-Hinds
Description	Device Box, ElectroGalvanized and Aluminum Acrylic Paint, Deep, 3/4 In Trade Size, 1 Gang, 2 Hubs, 3/4 In Hub Size, End Hub Location, 2.75 In Width, 6.03 In Height, Surface Mount, 3.15 LB/Ea
Weight per unit	3.2 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

### Features

Cable Entry	(1) Each End
dimensions	6.0300 IN X 2.6900 IN X 2.7500 IN
Material	ElectroGalvanized With Aluminum Acrylic Painted Feraloy Iron Alloy

### Dimensions and Weight

Size	3/4 in
------	--------

### Descriptions

Description	3/4" 1G DEV BOX
extra long description	CRS-H FDC2 3/4 THRUFEED CST IRON BX
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Special Features	Configuration Type FDC, Dimension 2-3/4 In Width X 2-11/16 In Depth X 6-1/32 In Height

### Manufacturer Information

Brand	Eaton
GTIN	00782274398204
UPC	782274398204

### Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Type	DEVICE BOX



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

217 Innovation Way  
37075-0000, TN Hendersonville  
Phone: 615-991-2399  
Fax: 000-000-0000

## Packaging

Carton ..... 2

Weight Per each ..... 3.15

## Uses, Certifications, and Standards

Mounting ..... FLUSH

standard ..... UL 514, CSA C22.2, Federal Specification W-C-5860