



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## FLM2 2A 250V TD Midget Fuse

Littelfuse

|                  |   |
|------------------|---|
| Catalog Number   | FLM2  |
| Manufacturer     | Littelfuse  |
| Description      | Use FLM 250 Volt Time-Delay Fuses to Protect Control Circuit Transformers, Solenoids, and Other Circuits With High Inrush Currents. Excellent For Supplemental Protection Of Small Motors. For Motor Branch-Circuit Protection, See Class CC Fuses. |
| Weight per unit  | 0.0100 (lbs/each)   |
| Product Category | Renewable & Non-Renewable   |

### Features

|                  |         |
|------------------|---------|
| interrupt rating | 10      |
| Voltage Rating   | 250 VAC |

### Descriptions

|                        |   |
|------------------------|---|
| Description            | 2A 250V TD MIDGET FUSE  |
| extra long description | LFSE FLM002 FUS 250V T/D MIDGET 2A  |
| Long Description       | Use FLM 250 volt time-delay fuses to protect control circuit transformers, solenoids, and other circuits with high inrush currents. Excellent for supplemental protection of small motors. For motor branch-circuit protection, see Class CC fuses. |
| Product Type           | Fus 250V T/D Midget 2a  |
| Special Features       | RoHS  |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | Littelfuse     |
| GTIN                      | 00079458140415 |
| Manufacturers Part Number | FLM002         |
| UPC                       | 079458140415   |

### Taxonomies, Classifications, and Categories

|                      |              |
|----------------------|--------------|
| Category Description | MIDGET FUSES |
| Type                 | Time-Delay   |

### Packaging

|                 |      |
|-----------------|------|
| Carton          | 1    |
| Package         | 10   |
| Weight Per each | 0.01 |

### Uses, Certifications, and Standards

|             |                          |
|-------------|--------------------------|
| Application | small motors/high inrush |
|-------------|--------------------------|