



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

FP3011448CLEAR Thin-Wall Heat Shrink Tubing, 1/4 - 48", CL *Minnesota Mining (3M)*

Catalog Number	FP3011448CLEAR
Manufacturer	Minnesota Mining (3M)
Description	Thin Wall Shrink Tube, Polyolefin Material, Clear, 2400 Psi Tensile Strength, 400 % Elongation At Break, 600 V, 1/4 In Cable Size, 0.125 In;3.18 MM Recovered Diameter, 0.25 In Expanded Diameter, 2:1 Shrink Ratio, -67 °F Operating Temperature, +275 °F Operating Temperature, 4 FT Length, 0.025 In Thickness, 10 Yr Shelf Life, 0.1 LB/Ea
Weight per unit	0.7510 (lbs/each)
Product Category	Insulating Materials

Descriptions

Description	THIN-WALL HEAT SHRINK TUBING, 1/4 - 48", CL
extra long description	3M 7000133496 3M™ Heat Shrink Thin-

Manufacturer Information

GTIN	00051128595787
Manufacturers Part Number	FPO.250CR48"S
UPC	051128595787

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Single (Thin) Wall

Packaging

Carton	1
Package	12
Weight Per each	0.751

Uses, Certifications, and Standards

standard	UL, CSA, ABS
----------	--------------