

ELLIOTT ELECTRIC SUPPLY 1570 Lionel Drive 79936-0000, TX El Paso

We Deliver...Lower Cost, Quality Products, & Personal Service

Phone: 915-995-8443 Fax: 915-245-2106



FP3011448RED Thin-Wall Heat Shrink Tubing, 1/4 - 48", RD *Minnesota Mining (3M)*

Catalog Number	FP3011448RED
Manufacturer	Minnesota Mining (3M)
Description	3M 7000133554 3M™ Heat Shrink Thin-
Weight per unit	0.0751 (lbs/each)
Product Category	Splicing & Terminating Kits

Descriptions

Description	THIN-WALL HEAT SHRINK TUBING, 1/4 - 48", RD
Features	3M™ Heat Shrink Tubing FP-301 is color coded for quick and easy
	identification of the wire. This split resistant, flame retardant
	tubing is used as shrink fit, electrical insulation over cable splices
	or terminations. The high expansion ratio tubing is mechanically
	tough, easily markable and resists cold flow. It is ideal for
	lightweight wire harness covering, fire resistant covering, wire
	marking, wire bundling and component packaging. It withstands
	temperatures of 67 to 275 degrees F (55 to 135 degrees
Long Description	3M 7000133554 3M™ Heat Shrink Thin-
Product Type	3M™ Heat Shrink Thin-Wall Flexible Polyolefin Tubing FP-301
Special Features	Flexible, Polyolefin

Manufacturer Information

Brand	3M	
GTIN	00051128596579	
Manufacturers Part Number	FP0.250RD48"H	
UPC	051128596579	

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Туре	Single (Thin) Wall

Availability

Manufacturer Status	Inactive
Status	Inactive

Packaging

Carton	12
Weight Per each	0.0751

Uses, Certifications, and Standards

standard	UL, CSA, ABS	