


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Product Type

FRNR225 225A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

I	
Catalog Number	FRNR225
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRN-R, Time-Delay, Dual-Element, Current Limiting Fuse, 225 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 250 Vac and 20 Ka At 250 VDC
Weight per unit	1.9 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	225
connection	Dlade End V Dlade End
dimensions	2.0000 IN X 0.5600 IN X 0.5600 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	200 kAIC at 250 Vac20 kAIC at 125 Vdc
media	Yes
Response Time	10 S at 500%
Voltage Rating	250 VAC, 125 VDC
Dimensions and Weight	
Size	2.38 In Diameter X 8.63 In Length
Descriptions	
Description	225A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-225 FUSETRON DUAL-ELEMEN
Features	Bussmann's UL Class RK5 Fusetron product offering provides energy efficient advanced protection with its dual-element, time-delay construction and is available with optional open fuse indication on select ratings. Available in both 250Vac and 600Vac, 200kA RMS Sym interrupting rating and sizes ranging from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay, dual-element, current limiting fuse, 225 A, non-indicating fuse, interrupting rating of 200 kA at 250 Vac and 20 kA at 250 Vdc

Fusetron Dual-Element



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	Eaton	
GTIN	00051712507493	
Manufacturers Part Number	FRN-R-225	
UPC	051712507493	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

onaging	
Carton	1
Weight Per each	1.93

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked