

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRNR80 80A 250V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

Catalog Number	FRNR80
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRN-R, Time-Delay, Dual-Element, Current Limiting Fuse, 80 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 250 Vac
Weight per unit	0.3200 (lbs/each)
Product Category	Dual Element
Features	
amperage rating	80 A
class	Class RK5
connection	
dimensions	5.8800 IN X 1.0000 IN X 1.0000 IN
element	Dual
Fuse Class	Class RK5
interrupt rating	200 kAIC at 250 Vac20 kAIC at 125 Vdc
media	
Response Time	
Voltage Rating	250 VAC, 125 VDC
Dimensions and Weight	
Size	1.06 In Diameter X 5.88 In Length
Descriptions	
Description	80A 250V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRN-R-80 FUSETRON DUAL-ELEMENT
Features	Bussmann's UL Class RK5 Fusetron product offering provides
	energy efficient advanced protection with its dual-element,
	time-delay construction and is available with optional open fuse
	indication on select ratings. Available in both 250Vac and
	600Vac, 200kA RMS Sym interrupting rating and sizes ranging
	from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of
	time-delay at 500 of rated current (8 seconds for 1/10-30A sizes)
Long Description	Eaton Bussmann Series Class RK5 fuse, FRN-R, time-delay,
	dual-element, current limiting fuse, 80 A, non-indicating fuse,
	interrupting rating of 200 kA at 250 Vac
Product Type	Fusetron Dual-Element Class RK5



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00051712507417
Manufacturers Part Number	FRN-R-80
UPC	051712507417
Taxonomies, Classifications, and C	ategories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	5
Weight Per each	0.32
Uses, Certifications, and Standards	S
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked