



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4406 Highway 28 East
71360-0000, LA Pineville
Phone: 318-767-0900
Fax: 318-767-0010



FSQC2320 2W-3P RCPT *Crouse-Hinds*

Catalog Number	FSQC2320
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Arktite FSQC Interlocked Receptacle With Switch, 30A, Through Feed, Two-Wire, Three-Pole, Brass Contacts, Copper-Free Aluminum, Spring Door, 3/4", Two-Pole Switch, 120-600 Vac
Weight per unit	5.4 (lbs/each)
Product Category	Pin & Sleeve Devices

Features

dimensions	4.7500 IN X 5.7500 IN X 10.0000 IN
insulation	Krydon
Voltage Rating	120/240/480/600 V

Dimensions and Weight

Width	5.75
-------	------

Descriptions

Description	2W-3P RCPT
extra long description	CRS-H FSQC2320 30A 2W3P ARK DF INTL
Features	Crouse-Hinds series Arktite FSQC interlocked receptacles are used to supply power to portable electrical equipment, such as hand lamps, lighting systems, power tools, conveyors and welders. Applicable in areas which are hazardous due to the presence of flammable vapors or gases and combustible dusts. Ideal for petroleum refineries, chemical and petrochemical plants, and facilities for processing and handling grain, flour and starch.
Long Description	Eaton Crouse-Hinds series Arktite FSQC interlocked receptacle with switch, 30A, Through feed, Two-wire, three-pole, Brass contacts, Copper-free aluminum, Spring door, 3/4", Two-pole switch, 120-600 Vac
Product Type	30A 2W3P Ark DF Intlck RCPT Thru Hub 3/4
Special Features	With Spring Door, 3/4 In Hub, NEMA/EEMAC 3/7B/7C/7D/9F/9G/12 Enclosure

Manufacturer Information

Brand	Eaton
GTIN	00782274417318
Manufacturers Part Number	FSQC2320
UPC	782274417318



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4406 Highway 28 East
71360-0000, LA Pineville
Phone: 318-767-0900
Fax: 318-767-0010

Taxonomies, Classifications, and Categories

Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Type	Interlocked receptacle with switch

Packaging

Carton	1
Weight Per each	5.4

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
standard	UL 1010, CSA C22.2, CUL C22.2