

# Specifications



## Eaton GBB-12-R

Eaton GBB Series Very fast-acting fuse, 1A, 250 Vac, 125 Vdc

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series very fast-acting fuse
<b>CATALOG NUMBER</b>	GBB-12-R
<b>UPC</b>	051712549899
<b>EAN</b>	5027590246774
<b>PRODUCT HEIGHT</b>	32 mm
<b>PRODUCT DIAMETER</b>	6 mm
<b>PRODUCT WEIGHT</b>	1.36 g
<b>COMPLIANCES</b>	RoHS Compliant CE Marked
<b>GLOBAL CATALOG</b>	GBB-12-R



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	12 A
<b>RESISTANCE</b>	0.0062 ohms DC cold
<b>VOLTAGE DROP</b>	0.0806 mV typical
<b>INTERRUPT RATING</b>	200 AIC at 250 Vac 10 kAIC at 125 Vac/dc
<b>FUSE INDICATOR</b>	Non-indicating
<b>CONNECTION</b>	Ferrule end x ferrule end
<b>RESPONSE TIME</b>	2 min at 150%, 1 sec at 250%
<b>MATERIAL</b>	Nickel-plated brass end cap construction Ceramic tube
<b>QUANTITY</b>	5
<b>VOLTAGE RATING</b>	250 Vac, 125 Vdc
<b>TYPE</b>	Electronic
<b>APPLICATION</b>	Electronic circuits

## Resources

PEP ECO-PASSPORT	<a href="#">EATO-00034-V01.01-EN</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton GBB ceramic tube fuses data sheet</a>
	<a href="#">Eaton Specification Sheet - GBB-12-R</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.



# Specifications



## Eaton GBB-12-R

Eaton GBB Series Very fast-acting fuse, 1A, 250 Vac, 125 Vdc

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series very fast-acting fuse
<b>CATALOG NUMBER</b>	GBB-12-R
<b>UPC</b>	051712549899
<b>EAN</b>	5027590246774
<b>PRODUCT HEIGHT</b>	32 mm
<b>PRODUCT DIAMETER</b>	6 mm
<b>PRODUCT WEIGHT</b>	1.36 g
<b>COMPLIANCES</b>	RoHS Compliant CE Marked
<b>GLOBAL CATALOG</b>	GBB-12-R



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	12 A
<b>RESISTANCE</b>	0.0062 ohms DC cold
<b>VOLTAGE DROP</b>	0.0806 mV typical
<b>INTERRUPT RATING</b>	200 AIC at 250 Vac 10 kAIC at 125 Vac/dc
<b>FUSE INDICATOR</b>	Non-indicating
<b>CONNECTION</b>	Ferrule end x ferrule end
<b>RESPONSE TIME</b>	2 min at 150%, 1 sec at 250%
<b>MATERIAL</b>	Nickel-plated brass end cap construction Ceramic tube
<b>QUANTITY</b>	5
<b>VOLTAGE RATING</b>	250 Vac, 125 Vdc
<b>TYPE</b>	Electronic
<b>APPLICATION</b>	Electronic circuits

## Resources

PEP ECO-PASSPORT	<a href="#">EATO-00034-V01.01-EN</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton GBB ceramic tube fuses data sheet</a>
	<a href="#">Eaton Specification Sheet - GBB-12-R</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

