



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



GDA3.15A 250V Fast Acting Fuse

Bussmann Fuses

Catalog Number	GDA3.15A
Manufacturer	Bussmann Fuses
Description	Eaton GDA Series Fast-Acting Fuse 3.15A, 250 Vac, 32 VDC (Self Certified), GDA-3-15a
Weight per unit	0.0060 (lbs/each)
Product Category	Small Dimension Fuses

Features

amperage rating	3.15
connection	Ferrule
dimensions	0.2047 IN X 0.2047 IN X 0.7874 IN
interrupt rating	1.5
Material	Ceramic tube/Nickel-plated brass end cap construction
type of indicators	Non-Indicating
Voltage Rating	250 Vac, 32 Vdc (self certified)

Dimensions and Weight

Size	5.20 mm Diameter X 20.00 mm Height
------	------------------------------------

Descriptions

Description	250V FAST ACTING FUSE
extra long description	EFSE GDA-3.15A BUSS SMALL DIMENSION
Features	Fast-acting, high breaking capacity 5 mm x 20 mm ferrule fuse designed to IEC 60127-2 for overcurrent protection of electronic circuits. Install into a Bussmann Series fuse holder, block or fuse clip. Also available axial leads for thru-hole installation. Eaton's GSA fast-acting, high breaking capacity 5mm x 20mm ferrule fuses are designed to IEC 60127-2 for overcurrent protection of electronic circuits. Order in cartridge fuse format and install into a Bussmann Series fuse holder, block, or fuse clip, or
Long Description	Eaton GDA Series Fast-acting fuse 3.15A, 250 Vac, 32 Vdc (self certified), GDA-3-15A
Product Type	Buss Small Dimension Fuse
Special Features	High Breaking Capacity, Interrupt Rating 1500 Amp at 250 Vac, Material Ceramic Tube, Nickel Plated Brass Endcap

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712431347
Manufacturers Part Number	GDA3.15A
UPC	051712431347



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	GLASS FUSES (and ceramic)
Type	Fast-Acting Fuse

Packaging

Carton	5
Weight Per each	0.006

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
Frequency Rating	50 HZ
standard	VDE,CE Marked,CCC Marked