

# Specifications



Photo is representative



## Eaton GDB-250MA

Eaton GDB Series Fast-acting fuse, 0.250A, 250 Vac or less, 32 Vdc (self certified)

### General specifications

|                         |                                            |
|-------------------------|--------------------------------------------|
| <b>PRODUCT NAME</b>     | Eaton Bussmann series GDB fast-acting fuse |
| <b>CATALOG NUMBER</b>   | GDB-250MA                                  |
| <b>UPC</b>              | 051712431705                               |
| <b>PRODUCT HEIGHT</b>   | 20 mm                                      |
| <b>PRODUCT DIAMETER</b> | 5.2 mm                                     |
| <b>PRODUCT WEIGHT</b>   | 0.7 g                                      |
| <b>WARRANTY</b>         | Not Applicable                             |
| <b>COMPLIANCES</b>      | CCC Marked<br>CE Marked<br>RoHS Compliant  |
| <b>CERTIFICATIONS</b>   | VDE                                        |
| <b>GLOBAL CATALOG</b>   | GDB-250MA                                  |



Powering Business Worldwide

## Product specifications

|                        |                                                        |
|------------------------|--------------------------------------------------------|
| AMPERAGE RATING        | 0.250A                                                 |
| FREQUENCY RATING - MAX | 50 Hz                                                  |
| FREQUENCY RATING - MIN | 50 Hz                                                  |
| VOLTAGE DROP           | 1400 mV maximum                                        |
| INTERRUPT RATING       | 35 AIC at 250 Vac                                      |
| FUSE INDICATOR         | Non-indicating                                         |
| CONNECTION             | Ferrule end x ferrule end                              |
| MATERIAL               | Glass tube<br>Nickel-plated brass end cap construction |
| QUANTITY               | 5                                                      |
| VOLTAGE RATING         | 250 Vac or less, 32 Vdc (self certified)               |
| TYPE                   | Electronic                                             |
| APPLICATION            | Electronic circuits                                    |

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton GDB fast-acting glass tube fuses data sheet](#)

[Eaton Specification Sheet - GDB-250MA](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.



# Specifications



Photo is representative



## Eaton GDB-250MA

Eaton GDB Series Fast-acting fuse, 0.250A, 250 Vac or less, 32 Vdc (self certified)

### General specifications

|                         |                                            |
|-------------------------|--------------------------------------------|
| <b>PRODUCT NAME</b>     | Eaton Bussmann series GDB fast-acting fuse |
| <b>CATALOG NUMBER</b>   | GDB-250MA                                  |
| <b>UPC</b>              | 051712431705                               |
| <b>PRODUCT HEIGHT</b>   | 20 mm                                      |
| <b>PRODUCT DIAMETER</b> | 5.2 mm                                     |
| <b>PRODUCT WEIGHT</b>   | 0.7 g                                      |
| <b>WARRANTY</b>         | Not Applicable                             |
| <b>COMPLIANCES</b>      | CCC Marked<br>CE Marked<br>RoHS Compliant  |
| <b>CERTIFICATIONS</b>   | VDE                                        |
| <b>GLOBAL CATALOG</b>   | GDB-250MA                                  |



Powering Business Worldwide

## Product specifications

|                        |                                                        |
|------------------------|--------------------------------------------------------|
| AMPERAGE RATING        | 0.250A                                                 |
| FREQUENCY RATING - MAX | 50 Hz                                                  |
| FREQUENCY RATING - MIN | 50 Hz                                                  |
| VOLTAGE DROP           | 1400 mV maximum                                        |
| INTERRUPT RATING       | 35 AIC at 250 Vac                                      |
| FUSE INDICATOR         | Non-indicating                                         |
| CONNECTION             | Ferrule end x ferrule end                              |
| MATERIAL               | Glass tube<br>Nickel-plated brass end cap construction |
| QUANTITY               | 5                                                      |
| VOLTAGE RATING         | 250 Vac or less, 32 Vdc (self certified)               |
| TYPE                   | Electronic                                             |
| APPLICATION            | Electronic circuits                                    |

## Resources

### SPECIFICATIONS AND DATASHEETS

[Eaton GDB fast-acting glass tube fuses data sheet](#)

[Eaton Specification Sheet - GDB-250MA](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

