



Circuit Guard® Bulk Pack GFCI Receptacles

Description	Rating	Color	Catalog Number	
Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple. Bulk packed, (50 pieces without wallplate).	15 and 20A 125V AC	Black	GF15BKLABULK	GF20BKLABULK
		Brown	GF15LABULK	GF20LABULK
		Gray	GF15GYLABULK	GF20GYLABULK
		Ivory	GF15ILABULK	GF20ILABULK
		Light Almond	GF15LALABULK	GF20LALABULK
		Red	GF15RLABULK	GF20RLABULK
		White	GF15WLABULK	GF20WLABULK



GF15BKLABULK



GF20GYLABULK



GFBF20ILA

Circuit Guard® Faceless GFCI

Description	Rating	Color	Catalog Number	
Faceless, nylon top, back and side wired, multiple drive screws, self-grounding staple.	20A 125V AC	Black	-	GFBF20BKLA
		Brown	-	GFBF20LA
		Gray	-	GFBF20GYLA
		Ivory	-	GFBF20ILA
		Light Almond	-	GFBF20LALA
		Red	-	GFBF20RLA
		White	-	GFBF20WLA

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles listed above are furnished with a matching color nylon wallplate.

Combination Switch/GFCI

Description	Rating	Color	Catalog Number	
Single-pole switch, GFCI grounding receptacle, back and side wired, matching nylon wallplate included.	15A 120V (Switch) 15A 125V (Receptacle)	Ivory	GFSP15IC	-
		Light Almond	GFSP15LAC	-
		White	GFSP15WC	-



GFSP15WC

GFCI Receptacle Specifications per GFCI Products Listed (Pages K-2 to K-9)

Trip Level	4 to 6 mA.
Trip Time	.025 second nominal.
Frequency	60 Hz.
Voltage	120V AC +10% - 15% (102V to 132V).
Amperage	15A/20A, 20A Feed Thru.
Maximum Interrupting Capacity	10,000A.
Operating Temperature	-35°C to 66°C or -30°F to 150°F.
Maximum Humidity	95%.
Listings and Standards	Meets UL498 for receptacles, UL943 Class A for GFCIs UL File E41978. CSA Certified.
Codes	Meets all NEC® and CEC requirements. NEMA WD-6 ANSI 73.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).

Safety and Economy



GF15ILA

10kA Short Circuit Current Rating

- Comprehensive diagnostics
 - When test button is actuated, both the electronic components and mechanical trip mechanism are functionally tested
- Ground fault indicator
 - Flashing **RED** indicates device has lost capability to provide protection
- No power at face if reverse wired
 - Open circuit condition eliminates false assumption of protection at face
- Installation ease
 - Internal back wiring
 - Automatic grounding feature
 - Captive mounting screws



GF15ILA







GFTR20I



GF20ILA

GFCI Duplex Receptacles, Flush Nylon Face, Matching Nylon Wallplate Included

Description	 Weather and Tamper-Resistant	 15A 125V NEMA 5-15R UL/CSA Standard	 Weather and Tamper-Resistant	 20A 125V NEMA 5-20R UL/CSA Standard
	Termination	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire
Rating	15A 125V AC NEMA 5-15R	15A 125V AC NEMA 5-15R	20A 125V AC NEMA 5-20R	20A 125V AC NEMA 5-20R
Black	GFTR15BK	GF15BKLA	GFTR20BK	GF20BKLA
Brown	GFTR15	GF15LA	GFTR20	GF20LA
Gray	GFTR15GY	GF15GYLA	GFTR20GY	GF20GYLA
Ivory	GFTR15I	GF15ILA	GFTR20I	GF20ILA
Light Almond	GFTR15LA	GF15LALA	GFTR20LA	GF20LALA
Red	GFTR15R	GF15RLA	GFTR20R	GF20RLA
White	GFTR15W	GF15WLA	GFTR20W	GF20WLA

Note: See page Tech-10 for Weather and Tamper-Resistant descriptions.
 Bulk 50 pack available without plates, add **"BULK"** suffix. Example: **GFTR20WBULK**.

GFCI Faceless Receptacles, Flush Nylon Face, Matching Nylon Wallplate Included

Description	Circuit Guard® Faceless
Termination	Self-Grounding, Back and Side Wire
Rating	20A 125V NEMA 5-20R
Black	GF20BKLA
Brown	GF20LA
Gray	GF20GYLA
Ivory	GF20ILA
Light Almond	GF20LALA
Red	GF20RLA
White	GF20WLA



15A 125V
 NEMA 5-15R
 UL CSA
 0.5 HP



20A 125V
 NEMA 5-20R
 UL CSA
 1 HP

Circuit Guard® Bulk Pack GFCI Receptacles

Description	Rating	Color	Catalog Number	
Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple. Bulk packed, (50 pieces without wallplate).	15 and 20A 125V AC	Black	GF15BKLABULK	GF20BKLABULK
		Brown	GF15LABULK	GF20LABULK
		Gray	GF15GYLABULK	GF20GYLABULK
		Ivory	GF15ILABULK	GF20ILABULK
		Light Almond	GF15LALABULK	GF20LALABULK
		Red	GF15RLABULK	GF20RLABULK
		White	GF15WLABULK	GF20WLABULK



GF15BKLABULK



GF20GYLABULK



GFBF20ILA

Circuit Guard® Faceless GFCI

Description	Rating	Color	Catalog Number	
Faceless, nylon top, back and side wired, multiple drive screws, self-grounding staple.	20A 125V AC	Black	-	GFBF20BKLA
		Brown	-	GFBF20LA
		Gray	-	GFBF20GYLA
		Ivory	-	GFBF20ILA
		Light Almond	-	GFBF20LALA
		Red	-	GFBF20RLA
		White	-	GFBF20WLA

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles listed above are furnished with a matching color nylon wallplate.

Combination Switch/GFCI

Description	Rating	Color	Catalog Number	
Single-pole switch, GFCI grounding receptacle, back and side wired, matching nylon wallplate included.	15A 120V (Switch) 15A 125V (Receptacle)	Ivory	GFSP15IC	-
		Light Almond	GFSP15LAC	-
		White	GFSP15WC	-



GFSP15WC

GFCI Receptacle Specifications per GFCI Products Listed (Pages K-2 to K-9)

Trip Level	4 to 6 mA.
Trip Time	.025 second nominal.
Frequency	60 Hz.
Voltage	120V AC +10% - 15% (102V to 132V).
Amperage	15A/20A, 20A Feed Thru.
Maximum Interrupting Capacity	10,000A.
Operating Temperature	-35°C to 66°C or -30°F to 150°F.
Maximum Humidity	95%.
Listings and Standards	Meets UL498 for receptacles, UL943 Class A for GFCIs UL File E41978. CSA Certified.
Codes	Meets all NEC® and CEC requirements. NEMA WD-6 ANSI 73.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).

Safety and Economy



GF15ILA

10kA Short Circuit Current Rating

- Comprehensive diagnostics
 - When test button is actuated, both the electronic components and mechanical trip mechanism are functionally tested
- Ground fault indicator
 - Flashing **RED** indicates device has lost capability to provide protection
- No power at face if reverse wired
 - Open circuit condition eliminates false assumption of protection at face
- Installation ease
 - Internal back wiring
 - Automatic grounding feature
 - Captive mounting screws



GF15ILA







GFTR20I



GFBF20ILA

GFCI Duplex Receptacles, Flush Nylon Face, Matching Nylon Wallplate Included

Description	 Weather and Tamper-Resistant	 15A 125V NEMA 5-15R UL/CSA Standard	 Weather and Tamper-Resistant	 20A 125V NEMA 5-20R UL/CSA Standard
	Termination	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire	Self-Grounding, Back and Side Wire
Rating	15A 125V AC NEMA 5-15R	15A 125V AC NEMA 5-15R	20A 125V AC NEMA 5-20R	20A 125V AC NEMA 5-20R
Black	GFTR15BK	GF15BKLA	GFTR20BK	GF20BKLA
Brown	GFTR15	GF15LA	GFTR20	GF20LA
Gray	GFTR15GY	GF15GYLA	GFTR20GY	GF20GYLA
Ivory	GFTR15I	GF15ILA	GFTR20I	GF20ILA
Light Almond	GFTR15LA	GF15LALA	GFTR20LA	GF20LALA
Red	GFTR15R	GF15RLA	GFTR20R	GF20RLA
White	GFTR15W	GF15WLA	GFTR20W	GF20WLA

Note: See page Tech-10 for Weather and Tamper-Resistant descriptions.
 Bulk 50 pack available without plates, add **"BULK"** suffix. Example: **GFTR20WBULK**.

GFCI Faceless Receptacles, Flush Nylon Face, Matching Nylon Wallplate Included

Description	Circuit Guard® Faceless
Termination	Self-Grounding, Back and Side Wire
Rating	20A 125V NEMA 5-20R
Black	GFBF20BKLA
Brown	GFBF20LA
Gray	GFBF20GYLA
Ivory	GFBF20ILA
Light Almond	GFBF20LALA
Red	GFBF20RLA
White	GFBF20WLA