



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1308 East 4th Street
79720-0000, TX Big Spring
Phone: 432-264-0316
Fax: 432-264-0483



GMA15R 15A 125V Fa 5X20MM Glass Fuse

Bussmann Fuses

Catalog Number	GMA15R
Manufacturer	Bussmann Fuses
Description	Eaton Gma Series Fast-Acting Fuse, 15A, 125 Vac, 32 VDC
Weight per unit	0.0020 (lbs/each)
Product Category	Small Dimension Fuses

Features

amperage rating	15 A
connection	Ferrule End X Ferrule End
dimensions	X X 0.7874 IN
interrupt rating	150 AIC at 125 Vac
Material	Glass tubeNickel-plated brass end cap construction
Response Time	60 min at 135%, 2 min at 200%
Voltage Rating	125 Vac, 32 Vdc

Dimensions and Weight

Size	5.20 mm Diameter X 20.00 mm Height
------	------------------------------------

Descriptions

Description	15A 125V FA 5X20MM GLASS FUSE
extra long description	BUSS GMA-15-R GMA 15A BUSS FUSE
Features	Fast-acting, glass tube 5 mm x 20 mm ferrule fuse designed to UL 248-14 for overcurrent protection of electronic circuits. Install into a Bussmann Series fuse holder, block or fuse clip. Also available with axial leads for thru-hole installation Eaton's GMA fast-acting, glass tube 5mm x 20mm ferrule fuses are designed to UL 248-14 for overcurrent protection of electronic circuits. Order in cartridge fuse format and install into a Bussmann Series fuse holder, block, or fuse clip, or purchase with available
Long Description	Eaton GMA Series Fast-acting fuse, 15A, 125 Vac, 32 Vdc
Product Type	Gma 15A Buss Fuse
Special Features	Low Breaking Capacity, Interrupt Rating 150 Amp at 125 Vac, Material Glass Tube, Nickel Plated Brass Endcap, ROHS Compliant

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712647878
Manufacturers Part Number	GMA-15-R
UPC	051712647878

Taxonomies, Classifications, and Categories

Category Description	GLASS FUSES (and ceramic)
Type	Fast-Acting Fuse



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1308 East 4th Street
79720-0000, TX Big Spring
Phone: 432-264-0316
Fax: 432-264-0483

Packaging

Carton	5
Weight Per each	0.002

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked,RoHS Compliant