

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Catalog Number	GRLB75A
Manufacturer	Appleton/Oz Gedney
Description	Unilets Outlet Box, Number Of Outlet: 2, Material: Copperfree (4/10 Of 1 PCT Maximum) Aluminum, Size: 3/4 In, Cable Entry: (2) 3/4 In GRLB Hub, Cubic Capacity: 18 Cu-In, Knockouts: No, Cover Opening: 3.38 In, Form Number: 1, Height: 3-3/
Weight per unit	1.2 (lbs/each)
Product Category	Alum
Features	
Cable Entry	(2) 3/4 IN GRLB Hub
Knockouts	FALSE
Material	Copperfree (4/10 Of 1 PCT Maximum) Aluminum
number of outlet	2
Dimensions and Weight	
Depth	3/4
Descriptions	
Description	3/4" ALU UNILET
extra long description	APP GRLB75-A 3/4 GR UNILET
Long Description	UNILETS Outlet Box, Number Of Outlet: 2, Material: Copperfree (4/10 Of 1 PCT Maximum) Aluminum, Size: 3/4 IN, Cable Entry: (2) 3/4 IN GRLB Hub, Cubic Capacity: 18 CU-IN, Knockouts: No, Cover Opening: 3.38 IN, Form Number: 1, Height: 3-3/
Product Type	3/4 GR Unilet
Special Features	Accommodate sealing, dome, hub and union hub covers and canopies; Accurately tapped, tapered hub threads for tight, rigid joints and ground continuity; Complies with a wide range of classified area requirements; Connect conduit lengths and change direction of conduit runs; Corrosion-resistant ideal indoors or out; Covers have pry notches for bar or wrench; Explosionproof, dust-ignitionproof; For pulling of wires; Function as sealing fittings when used with sealing covers; Furnished with copperfree (4/10 of 1 PCT ma



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information	
Brand	Appleton
GTIN	00781381443456
Manufacturers Part Number	GRLB75-A
UPC	781381443456
Taxonomies, Classifications, and (Categories
Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Туре	OUTLET BOX
Packaging	
Carton	1
Package	5
Weight Per each	1.15
Uses, Certifications, and Standard	ls
Application	For Use With Threaded Metal Conduit
standard	Class 1, Zone 1 And 2 IIA And IIB, UL File Number E10444, CSA

Class III

C22.2 No. 25, C22.2 No. 30, CSA 013017 Certified, Class I, Division 1 And 2, Groups B, C, D Class II, Division 1 And 2, Groups E, F, G