



## GUA26 3/4" Gua Cond Body&CVR

*Crouse-Hinds*

Catalog Number	GUA26
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Gua Conduit Outlet Box With Cover, 3" Cover Opening Diameter, Feraloy Iron Alloy, 3/4"
Weight per unit	2.2 (lbs/each)
Product Category	Bodies & Covers

### Features

Cable Entry dimensions	Dead End 4.3800 IN X 2.0000 IN X 3.5000 IN
------------------------	---

### Dimensions and Weight

Size	3/4 in
------	--------

### Descriptions

Construction	Explosionproof, Dust-Ignitionproof, Raintight
Description	3/4" GUA COND BODY&CVR
extra long description	CRS-H GUA26 3/4 OUTL BX 3 DIA CVR T
Features	Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th
Long Description	Eaton Crouse-Hinds series Condulet GUA conduit outlet box with cover, 3" cover opening diameter, Feraloy iron alloy, 3/4"
Product Type	3/4 Outl BX 3 Dia CVR THRD Rigid/Imc
Special Features	With Cover, Cover Opening Diameter 3 In

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274744834
Manufacturers Part Number	GUA26
UPC	782274744834

### Taxonomies, Classifications, and Categories

Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Type	Conduit outlet box with cover



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

700 Industry Way Suite 10  
75078-0000, TX Prosper  
Phone: 469-899-3981  
Fax: 469-899-3982

## Packaging

Carton	1
Package	2
Weight Per each	2.23

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting standard	PAD UL 886, CSA C22.2