



GUAC24 3/4" Guac Cond Body&CVR

Crouse-Hinds

Catalog Number	GUAC24
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Gua Conduit Outlet Box With Cover, 2" Cover Opening Diameter, Feraloy Iron Alloy, C Shape, 3/4"
Weight per unit	1.8 (lbs/each)
Product Category	Bodies & Covers

Features

Cable Entry	Feed Through
dimensions	4.2500 IN X 2.0000 IN X 2.5000 IN

Dimensions and Weight

Size	3/4 in
------	--------

Descriptions

Construction	Explosionproof, Dust-Ignitionproof, Raintight
Description	3/4" GUAC COND BODY&CVR
extra long description	CRS-H GUAC24 3/4 OUTL BX 2 DIA CVR
Features	Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th
Long Description	Eaton Crouse-Hinds series Condulet GUA conduit outlet box with cover, 2" cover opening diameter, Feraloy iron alloy, C shape, 3/4"
Product Type	3/4 Outl BX 2 Dia CVR THRD Rigid/Imc
Special Features	With Cover, Cover Opening Diameter 2 In

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274462202
Manufacturers Part Number	GUAC24
UPC	782274462202

Taxonomies, Classifications, and Categories

Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Type	Conduit outlet box with cover



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

12555 Harris Branch Pkwy Suite 105
78653-0000, TX Manor
Phone: 512-339-8750
Fax: 512-339-6732

Packaging

Carton	1
Package	2
Weight Per each	1.83

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting standard	PAD UL 886, CSA C22.2