

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

320 N Simon Sager Ave 72761-0000, AR Siloam Springs Phone: 479-238-1561 Fax: 479-238-1461



### **GUAC26 3/4" Guac Conduit Outlet Box** Crouse-Hinds

Catalog Number	GUAC26
Manufacturer	Crouse-Hinds
Description	Conduit Outlet Box With Cover, Electrogalvanized and Aluminum Acrylic Paint (Body); Natural (Cover), E Body Type, 3/4 In Trade Size, Threaded Connection, Round, 3 In (Cover) Opening Size, 2 Hubs, 3/4 In Hub Size, (2) Side Hub Location, E Configuration, 3-1/2 In Width, 2 In Height, (4) Pad, 2.33 LB/Ea
Weight per unit	2.3 (lbs/each)
Product Category	Bodies & Covers

#### **Features**

Cable Entry	Feed Through
dimensions	5 2500 IN X 2 0000 IN X 3 5000 IN

## **Dimensions and Weight**

Construction

Size	3/4 in
UILU	

## **Descriptions**

Description	3/4" GUAC CONDUIT OUTLET BOX
extra long description	CRS-H GUAC26 3/4 CST IRON ROUND BAS
Features	Crouse-Hinds series GUA and GUR explosionproof conduit outlet
	boxes are installed in conduit systems in hazardous areas to
	protect conductors in threaded rigid conduit, act as pull and
	splice boxes, change conduit direction, and provide access to
	conductors for maintenance and future system changes. GUA
	and GUR outlet boxes are certified for Class I, Division 1, Groups
	B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are
	available in ten different hub arrangements, maximizing

Explosionproof, Dust-Ignitionproof, Raintight

### **Manufacturer Information**

Brand	Eaton
GTIN	00782274462301
UPC	782274462301

flexibility in th

## Taxonomies, Classifications, and Categories

Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Туре	Conduit outlet box with cover

# **Packaging**

Carton 1 Package 2 Weight Per each 2 33	onaging		
	Carton	1	
Weight Per each 2.33	Package	2	
Weight of cach	Weight Per each	2.33	

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

320 N Simon Sager Ave 72761-0000, AR Siloam Springs Phone: 479-238-1561 Fax: 479-238-1461

**Uses, Certifications, and Standards** 

Mounting	PAD
standard	UL 886, CSA C22.2