

ELLIOTT ELECTRIC SUPPLY 4510 East Hwy 377 76049-0000, TX Granbury Phone: 817-573-0675

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 817-573-0776



GUAL16 1/2" Gual Conduit Outlet Box Crouse-Hinds

| Catalog Number | GUAL16 |
|------------------|---|
| Manufacturer | Crouse-Hinds |
| Description | Conduit Outlet Box With Cover, Electrogalvanized and Aluminum Acrylic Paint (Body); Natural (Cover), L Body Type, 1/2 In Trade Size, Threaded Connection, Round, 3 In (Cover) Opening Size, 2 Hubs, 1/2 In Hub Size, (2) Side Hub Location, L Configuration, 3-1/2 In Width, 2 In Height, (4) Pad, 2.25 LB/Ea |
| Weight per unit | 2.3 (lbs/each) |
| Product Category | Bodies & Covers |

Features

Cable Entry (2) Side 4.3800 IN X 2.0000 IN X 4.3800 IN dimensions

Dimensions and Weight

Size 1/2 in

Construction

Descriptions

| Description | 1/2" GUAL CONDUIT OUTLET BOX |
|------------------------|---|
| extra long description | CRS-H GUAL16 1/2 CST IRON ROUND BAS |
| Features | Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing |

Explosionproof, Dust-Ignitionproof, Raintight

flexibility in th

Manufacturer Information

| Brand | Eaton |
|-------|----------------|
| GTIN | 00782274464800 |
| UPC | 782274464800 |

Taxonomies, Classifications, and Categories

| Category Description | HUB STYLE BOXES (GUAB, GUAT, ETC) |
|----------------------|-----------------------------------|
| Туре | Conduit outlet box with cover |

Packaging

| Carton | 2 | |
|-----------------|------|--|
| Weight Per each | 2.25 | |

4510 East Hwy 377 76049-0000, TX Granbury Phone: 817-573-0675 Fax: 817-573-0776

| Uses, Certificat | tions, and | l Stand | ards |
|------------------|------------|---------|------|
|------------------|------------|---------|------|

standard UL 886, CSA C22.2