


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

700 Industry Way Suite 10 75078-0000, TX Prosper Phone: 469-899-3981





GUAW16 1/2" Guaw Cond Body&CVR *Crouse-Hinds*

Crouse-Hinas	
Catalog Number	GUAW16
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Gua Conduit Outlet Box With Cover, 3" Cover Opening Diameter, Feraloy Iron Alloy, W Shape, 1/2"
Weight per unit	2.8 (lbs/each)
Product Category	Bodies & Covers
Features	
Cable Entry	(3) Side, (1) Down
dimensions	5.2500 IN X 2.8800 IN X 4.3800 IN
Dimensions and Weight	
Size	1/2 in
Descriptions	
Construction	Explosionproof, Dust-Ignitionproof, Raintight
Description	1/2" GUAW COND BODY&CVR
extra long description	CRS-H GUAW16 1/2 OUTL BX 3 DIA CVR
Features	Crouse-Hinds series GUA and GUR explosionproof conduit outlet boxes are installed in conduit systems in hazardous areas to protect conductors in threaded rigid conduit, act as pull and splice boxes, change conduit direction, and provide access to conductors for maintenance and future system changes. GUA and GUR outlet boxes are certified for Class I, Division 1, Groups B, C, D and Class II, Division 1, Groups E, F, G. GUA boxes are available in ten different hub arrangements, maximizing flexibility in th
Long Description	Eaton Crouse-Hinds series Condulet GUA conduit outlet box with cover, 3" cover opening diameter, Feraloy iron alloy, W shape, 1/2"
Product Type	1/2 Outl BX 3 Dia CVR THRD Rigid/Imc
Special Features	With Cover, Cover Opening Diameter 3 In
Manufacturer Information	
Brand	Eaton
GTIN	00782274468303
Manufacturers Part Number	GUAW16
UPC	782274468303

Taxonomies, Classifications, and Categories

Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Туре	Conduit outlet box with cover



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

700 Industry Way Suite 10 75078-0000, TX Prosper Phone: 469-899-3981 Fax: 469-899-3982

_					•		
IJ.	7	`'	1	\sim		•	\sim
_	41	:k	7				
	шv	,,,	u	ч			ч

Carton	1	
Weight Per each	2.75	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	PAD
standard	UL 886, CSA C22.2