



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## H150GRTB 1-1/2" ZN Grounding Hub

*Abb Installation Products, Inc*

|                  |  |
|------------------|--|
| Catalog Number   | H150GRTB   |
| Manufacturer     | Abb Installation Products, Inc   |
| Description      | 1-1/2 Inch Zinc Grounding Hub With Thermoplastic Insulating Throat, Sealing Ring Nitrile (Buna-N) For Use With Rigid/Imc Conduit |
| Weight per unit  | 0.7400 (lbs/each)  |
| Product Category | Rigid Conduit Fittings - Steel   |

### Descriptions

|                        |  |
|------------------------|--|
| Description            | 1-1/2" ZN GROUNDING HUB  |
| extra long description | ABB H150GR-TB 1.5 INCH T&B ZINC GRO  |
| Long Description       | 1-1/2 Inch Zinc Grounding Hub with Thermoplastic Insulating Throat, Sealing Ring Nitrile (BUNA-N) for Use with Rigid/IMC Conduit |
| Product Type           | 1.5 Inch T&B Zinc Grounding Hub  |
| Special Features       | Hubs & Accessories   |

### Manufacturer Information

|                           |                 |
|---------------------------|-----------------|
| Brand                     | T&B Ind Fitting |
| GTIN                      | 00786210913711  |
| Manufacturers Part Number | H150GR-TB       |
| UPC                       | 786210913711    |

### Taxonomies, Classifications, and Categories

|                      |  |
|----------------------|--|
| Category Description | Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR |
| Type                 | Grounding Hub  |

### Trade Size

|            |          |
|------------|----------|
| Trade Size | 1-1/2 in |
|------------|----------|

### Packaging

|                 |      |
|-----------------|------|
| Carton          | 10   |
| Weight Per each | 0.74 |

### Uses, Certifications, and Standards

|             |                                |
|-------------|--------------------------------|
| Application | For use with rigid/IMC conduit |
| standard    | UL E23018, CSA                 |