

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2260 N Burton Ave Suite 100 65803-0000, MO Springfield Phone: 417-429-1665

Fax: 417-429-1666



HBL2633 LKG Conn, 30A 277V, L7-30R, B/W Hubbell Wiring Devices

Catalog Number	HBL2633
Manufacturer	Hubbell Wiring Devices
Description	Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 30A 277V Ac, 2-Pole 3-Wire Grounding, L7-30R, Screw Terminal, Black and White.
Weight per unit	0.3500 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out
atures amperage rating	30

Fea

atur 05	
amperage rating	30
connection	Pressure Screw Terminal
Current Rating	30
insulation	Insulated Body
Material	Nylon
Number of Conductors	3
pallet quantity	2880
Poles	2-Pole
Voltage Rating	277

Material, Color, and Finish

	•	-	
Co	lor		Black; White

Dimensions and Weight

Size	2.26 in x 2.26 in x 3.86 in
JIZC	2.20 III A 2.20 III A 3.00 III

Descriptions

Description	LKG CONN, 30A 277V, L7-30R, B/W
extra long description	HWDK HBL2633 LKG CONN, 30A 277V, L7
Long Description	Locking Devices, Twist-Lock®, Industrial, Female Connector Body, 30A 277V AC, 2-Pole 3-Wire Grounding, L7-30R, Screw Terminal, Black and White.
Product Type	LKG Conn, 30A 277V, L7-30R, B/W
Special Features	Standard Product

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585038971
Manufacturers Part Number	HBL2633
UPC	783585038971

Taxonomies, Classifications, and Categories

Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Туре	Connector Body



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2260 N Burton Ave Suite 100 65803-0000, MO Springfield Phone: 417-429-1665

Fax: 417-429-1666

_		
	ZAZIBA	•
241	K ALIIII III	1
uu	kaging	ı

Carton	1	
Package	30	
Weight Per each	0.35	

Uses, Certifications, and Standards

Application	Heavy Duty Industrial
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Cord
nema rating	L7-30R
standard	Certified to CSA, C22.2, No. 42;Fed.Spec. W-C-596;Listed to UL 498