

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Manufacturers Part Number

**UPC** 

## HBL2720 LKG RCPT, 30A 3P 250V, L15-30R, BK Hubbell Wiring Devices

Catalog Number	HBL2720	
Manufacturer	Hubbell Wiring Devices	
Description	Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 30A 3-Phase Delta 250V Ac, 3-Pole 4-Wire Grounding, L15-30R, Screw Terminal, Black.	
Weight per unit	0.3000 (lbs/each)	
Product Category	Gen Purpose Recept & Surge Pro	
Features		
amperage rating	30	
connection	Screw Terminal	
Current Rating	30	
Dielectric Strength	Withstands 2,000V minimum	
Material	Nylon	
Number of Wires		
pallet quantity	2520	
Phase	3	
Poles	3-Pole	
Voltage Rating	3 Phase 250 VAC	
Wattage	7,500	
Wire Size	#16 to #8	
<b>Dimensions and Weight</b>		
Size	3.28 in x 1.7 in x 1.31 in	
Descriptions		
Description	LKG RCPT, 30A 3P 250V, L15-30R, BK	
extra long description	HWDK HBL2720 LKG RCPT, 30A 3P 250V,	
Long Description	Locking Devices, Twist-Lock®, Industrial, Flush Receptacle, 30A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-30R, Screw Terminal, Black.	
Product Type	LKG RCPT, 30A 3P 250V, L15-30R, BK	
Special Features	Standard	
Manufacturer Information		
Brand	WIRING DEVICE-KELLEMS	
GTIN	00783585236131	

HBL2720

783585236131



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

<b>Taxonomies</b>	Classifications,	and Categori	ies
-------------------	------------------	--------------	-----

Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Туре	Single Flush Receptacle
Packaging	
Carton	1
Package	10
	0.3
Uses, Certifications, and Stand	dards

## Uses,

Application	Heavy Duty Industrial
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	L15-30R
standard	Certified to CSA C22.2 No.42;Fed.Spec. W-C-596;Listed to UL
	498;WR Rating