

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3101 Industrial Terrace 78758-0000, TX Austin Phone: 512-351-3290 Fax: 512-973-9027



HBL2723ST LKG Conn, 30A 3P 250V, L15-30R, SP T Hubbell Wiring Devices

Catalog Number	HBL2723ST
Manufacturer	Hubbell Wiring Devices
Description	Locking Devices, Edgeconnect™ Twist-Lock®, Industrial, Female Connector Body, 30A 3-Phase Delta 250V Ac, 3-Pole 4-Wire Grounding, L15-30R, Screwless Terminal, Black and White
Weight per unit	-
Product Category	
eatures	
connection	EdgeConnect™ Screwless Termination
Material	Nylon
pallet quantity	
Poles	3
Voltage Rating	3P 250
Material, Color, and Finish	
Color	Black;White
imensions and Weight	
Size	Standard Sized Product
escriptions	
Description	LKG CONN, 30A 3P 250V, L15-30R, SP T
extra long description	
Features	EdgeConnect™ Screwless Termination system, simply insert the
	wire and press the plunger down. No tools are required. That
	connection is fool-proof and long lasting, to all but guarantee a
	high quality result. Any qualified installer regardless of level of
	training can guarantee a high quality result.
Long Description	Locking Devices, EdgeConnect™ Twist-Lock®, Industrial, Female
	Connector Body, 30A 3-Phase Delta 250V AC, 3-Pole 4-Wire
	Grounding, L15-30R, Screwless Terminal, Black and White
Product Type	LKG Conn, 30A 3P 250V, L15-30R, SP T
Special Features	EdgeConnect™ Technology, Screwless Termination
Manufacturer Information	MIDNIO DELVIOE VELLENO
Brand	WIRING DEVICE-KELLEMS
GTIN	00783585719108
Manufacturers Part Number	HBL2723ST
series	EdgeConnect™ Twist-Lock® Series
UPC	783585719108



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3101 Industrial Terrace 78758-0000, TX Austin Phone: 512-351-3290 Fax: 512-973-9027

Taxonomies, Classifications, and Cate	egories
Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Туре	CONNECTOR
Packaging	
Carton	1
Package	30
Weight Per each	0.45
Uses, Certifications, and Standards	
environmental conditions	IP20 Suitability
Mounting	SCREW
nema rating	L15-30R
standard	Listed to UL 498, Fed.Spec. W-C-596, Certified to CSA C22.2

No.42