


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





HBL8300HI Dup RCPT, Com/HG, 20A 125V, 5-20R, Iv Hubbell Wiring Devices

d1005			
Catalog Number	HBL8300HI		
Manufacturer	Hubbell Wiring Devices		
Description	Straight Blade Devices, Receptacles, Duplex, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5- 20R, Ivory, Single Pack.		
Weight per unit			
Product Category			
eatures			
amperage rating	20		
connection	Dook and Cida Wined Consul Townsingle		
Current Rating	20		
Dielectric Strength			
Number of Wires			
pallet quantity			
Phase	1		
Poles	2-Pole		
Voltage Rating			
Wattage	2500		
Wire Size	#12 to #10		
imensions and Weight			
Size	3.28 in x 1.33 in x 1.05 in		
escriptions			
Description	DUP RCPT, COM/HG, 20A 125V, 5-20R, IV		
extra long description	HWDK HBL8300HI DUP RCPT, COM/HG, 20		
Features	HBL® Extra Heavy Duty Max Hospital Grade Devices - UL requirements for Hospital Grade devices is more stringent than those for standard devices. Hubbell receptacles are designed to meet and exceed the standards with Exclusive nickel-plated		
	bypass contact design increases contact pressure, lowering the operating temperature; Four point grounding system provides redundant grounding for low resistance ground continuity in high abuse areas; Impact resistant deep face design prevents breakage. Because of these		
Long Description	Straight Blade Devices, Receptacles, Duplex, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5- 20R, Ivory, Single		
	Pack.		
Product Type	Dup RCPT, Com/HG, 20A 125V, 5-20R, Iv		



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	WIRING DEVICE-KELLEMS	
GTIN	00783585015675	
Manufacturers Part Number	HBL8300HI	
series	Hospital Grade	
UPC	783585015675	

Taxonomies, Classifications, and Categories

Category Description	Industrial receptacles
Туре	RECEPTACLE

Packaging

Carton	1	
Package	10	
Weight Per each	0.082	

Uses, Certifications, and Standards

Application	Slender/Compact Hospital Grade	
environmental conditions	Indoor Dry unless protected by additional means	
Mounting	Screw Mount	
nema rating	5-20R	
standard	CSA Certified, C22.2, No. 42 File 285; Fed. Spec. W-C-596; NEMA®	
	WD-6 Compliant;UL Listed to UL498 File No. E2186	