

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

HBLDS30AC NM Sloped Disc, 30A Unfused, 4X, Hblac1 *Hubbell Wiring Devices*

Hubbell Willing Devices	
Catalog Number	HBLDS30AC
Manufacturer	Hubbell Wiring Devices
Description	Industrial Grade, Motor Disconnect, Unfused, 3 Pole, 30A 600V Ac, Screw Terminals, IP69K, Nema Type 4X, 12 Non-Metallic Sloped Top Enclosure, AC1 Aux Contact, Culus, NSF, Ce, UI 508 / UI 60947-4-1a
Weight per unit	2.9 (lbs/each)
Product Category	Distribution Equipment
Features	
Shape	Rounded Top
Material, Color, and Finish	
Color	Gray
Descriptions	
Description	NM SLOPED DISC, 30A UNFUSED, 4X, HBLAC1
extra long description	HWDK HBLDS30AC NM SLOPED DISC, 30A
Features	NEC section 430.102(B) requires each motor controller to have a disconnect within line of sight from the motor and driven
	equipment. Hubbell's Circuit-Lock® Unfused Disconnect Switches are UL listed as a manual motor controller and also "suitable as a motor disconnect" and meet these code requirements.
Long Description	Industrial Grade, Motor Disconnect, Unfused, 3 Pole, 30A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12 Non-Metallic
	Sloped Top Enclosure, AC1 Aux Contact, cULus, NSF, CE, UL 508 /
D. L. L.T.	UL 60947-4-1A
Product Type	NM Sloped Disc, 30A Unfused, 4X, Hblac1
Manufacturer Information	MUDINO DELUGE VELLENTO
Brand	WIRING DEVICE-KELLEMS
GTIN	00783585763033
Manufacturers Part Number	HBLDS30AC
series	Non-Fused
UPC	783585763033
Taxonomies, Classifications, and C	
Category Description	
Туре	Disconnect Switches
Packaging	
Carton	1

2.89

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Heavy Duty Industrial and/or Washdown
standard	cULus Listed