

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

706 Solon Rd. 75165-0000, TX Waxahachie Phone: 972-937-6965

Fax: 972-937-6968



series

UPC

HBLDS60100RS Rep Disco Switch, 60A, Hubbell Wiring Devices

| 33.33 | |
|------------------------------|---|
| Catalog Number | HBLDS60100RS |
| Manufacturer | Hubbell Wiring Devices |
| Description | Switches and Lighting Controls, Industrial Grade, Disconnect Switches, Replacement Switch, Three Pole, 60A 600V Ac, Screw Terminals, Gray |
| Weight per unit | 0.4530 (lbs/each) |
| Product Category | Non-Fusible Disconnect Safety |
| Features | |
| amperage rating | 60/100 |
| connection | Terminal Screws |
| Contact Configuration | Two Position |
| Contact Rating | 100A |
| Material | COMPOSITE |
| Poles | 3 |
| Dimensions and Weight | |
| Size | Standard Sized |
| Descriptions | |
| Description | REP DISCO SWITCH, 60A, |
| extra long description | HWDK HBLDS60100RS REP DISCO SWITCH, |
| Features | NEC section 430.102(B) requires each motor controller to have a disconnect within line of sight from the motor and driven equipment. Hubbell's Circuit-Lock® Unfused Disconnect Switches are UL listed as a manual motor controller and also "suitable as a motor disconnect" and meet these code requirements. |
| Long Description | Switches and Lighting Controls, Industrial Grade, Disconnect Switches, Replacement Switch, Three Pole, 60A 600V AC, Screw Terminals, Gray |
| Product Type | Rep Disco Switch, 60A, |
| Special Features | Standard Product |
| Manufacturer Information | |
| Brand | WIRING DEVICE-KELLEMS |
| GTIN | 00783585955216 |
| Manufacturers Part Number | HBLDS60100RS |
| | |

Fused; Non-Fused

783585955216



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

706 Solon Rd. 75165-0000, TX Waxahachie Phone: 972-937-6965 Fax: 972-937-6968

| Taxonomies, Classifications, and Categories | |
|---|---|
| Category Description | DISCONNECTS |
| Туре | Accessories |
| Packaging Carton | 1 |
| Package | 10 |
| Weight Per each | 0.453 |
| Uses, Certifications, and Standards | |
| Application | For 60 and 100A HBLDS6 Series |
| environmental conditions | Indoor Dry unless protected by additional means |

UL Listed