



## HST1.1485Y Heat Shrink Tubing

*Panduit Corporation*

Catalog Number	HST1.1485Y
Manufacturer	Panduit Corporation
Description	The HST1.1-48-5Y Thick Wall Heat Shrink Features An Adhesive Lined Inner Wall That Seals and Provides Excellent Protection Against Moisture. Applications Include Insulating and Protecting Wires/Cables In Outdoor, Wet Locations. Thick Wall For Direct Burial. Voltage Rating: UL 486D Listed For 600 V 90°C Continuous Use. Shrink Ratio: 3:1. Temperature Range: -67°F to 230°F (-55°C to 110°C). Cross-Linked Polyolefin. 1.1" (27.9 MM) Dia. 48" (1219.2 MM) Length. Color Black. 5 Per Package.
Weight per unit	2.8 (lbs/each)
Product Category	Insulating Materials

### Features

flammability	VW-1
media	Yes
outside diameter	1.1
Shrink Ratio	3:1

### Material, Color, and Finish

Color	Black
-------	-------

### Dimensions and Weight

Thickness	0.12
-----------	------

### Descriptions

Description	HEAT SHRINK TUBING
extra long description	PAN HST1.1-48-5Y Wet-Shrink™ HST1.1
Long Description	The HST1.1-48-5Y Thick Wall Heat Shrink features an adhesive lined inner wall that seals and provides excellent protection against moisture. Applications include insulating and protecting wires/cables in outdoor, wet locations. Thick wall for direct burial. Voltage rating: UL 486D Listed for 600 V 90°C continuous use. Shrink ratio: 3:1. Temperature range: -67°F to 230°F (-55°C to 110°C). Cross-linked Polyolefin. 1.1" (27.9 mm) dia. 48" (1219.2 mm) length. Color Black. 5 per package.
Product Type	Wet-Shrink™ HST1.1-48-5Y Heatshrink, BLK, Adh. Lined Po, 4'



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4075 Boulder Ridge Drive  
30336-0000, GA Atlanta  
Phone: 470-237-5352  
Fax: 470-237-5353

## Manufacturer Information

Brand	PANDUIT
GTIN	00074983107315
Manufacturers Part Number	HST1.1-48-5Y
UPC	074983107315

## Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Heat-Shrink

## Packaging

Carton	5
Weight Per each	2.75

## Uses, Certifications, and Standards

Application	For Wet Locations;Insulating and protecting wires and cables;Suitable for direct burial
standard	CSA: 244528;Mil Spec: AS23053;UL Listed: E173379;UL/UR: E342365;UL224 VW-1