



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln  
79109-3210, TX Amarillo  
Phone: 806-220-0404  
Fax: 806-220-0811



## **HSTT150485C HSTT150485C HT Shrink Tub** *Panduit Corporation*

Catalog Number	HSTT150485C
Manufacturer	Panduit Corporation
Description	The HSTT150-48-5C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Cross-Linked Polyolefin. 1.50" Diameter X 4' Long (38.1 MM X 1.2 M). Color Clear. 5 Per Package.
Weight per unit	1.0 (lbs/each)
Product Category	Insulating Materials

### **Features**

flammability	N/A
media	Yes
outside diameter	1.5
Shrink Ratio	2:1

### **Material, Color, and Finish**

Color	Colorless
-------	-----------

### **Dimensions and Weight**

Thickness	0.04
-----------	------

### **Descriptions**

Description	HSTT150485C HT SHRINK TUB
extra long description	PAN HSTT150-48-5C Dry-Shrink™ HSTT1
Long Description	The HSTT150-48-5C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Cross-linked polyolefin. 1.50" Diameter x 4' Long (38.1 mm x 1.2 m). Color Clear. 5 per package.
Product Type	Dry-Shrink™ HSTT150-48-5C Heatshrink, Clear, Po, 4' L, 1.5"



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln  
79109-3210, TX Amarillo  
Phone: 806-220-0404  
Fax: 806-220-0811

## Manufacturer Information

Brand	PANDUIT
GTIN	00074983906673
Manufacturers Part Number	HSTT150-48-5C
UPC	074983906673

## Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Heat-Shrink Tubing

## Packaging

Carton	50
Package	5
Weight Per each	1

## Uses, Certifications, and Standards

Application	For Dry Locations; Insulating and protecting wires and cables
standard	Mil Spec: AMS-DTL-23053/5 Class 2