



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

15152 E Fremont Dr  
80112-0000, CO Centennial  
Phone: 720-278-7555  
Fax: 720-259-8851

## **HSTT150C 1-1/2-3/4" 100' BLK Thinwall HS Tube** *Panduit Corporation*

|                  |  |
|------------------|--|
| Catalog Number   | HSTT150C   |
| Manufacturer     | Panduit Corporation  |
| Description      | The HSTT150-C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 1.50" Diameter X 100' Long (38.1 MM X 30.5 M). Color Black. 1 Roll. |
| Weight per unit  | 6.1 (lbs/each)   |
| Product Category | Insulating Materials   |

### **Features**

|                  |                 |
|------------------|-----------------|
| flammability     | Flame Retardant |
| media            | Yes             |
| outside diameter | 1.5             |
| Shrink Ratio     | 2:1             |

### **Material, Color, and Finish**

|       |       |
|-------|-------|
| Color | Black |
|-------|-------|

### **Dimensions and Weight**

|           |      |
|-----------|------|
| Thickness | 0.04 |
|-----------|------|

### **Descriptions**

|                        |  |
|------------------------|--|
| Description            | 1-1/2-3/4" 100' BLK THINWALL HS TUBE   |
| extra long description | PAN HSTT150-C Dry-Shrink™ HSTT150-C  |
| Long Description       | The HSTT150-C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 1.50" Diameter x 100' Long (38.1 mm x 30.5 m). Color Black. 1 roll. |
| Product Type           | Dry-Shrink™ HSTT150-C Heatshrink, Black, Po, 100' L, 1.5" to   |

### **Manufacturer Information**

|                           |                |
|---------------------------|----------------|
| Brand                     | Panduit®       |
| GTIN                      | 00074983914937 |
| Manufacturers Part Number | HSTT150-C      |
| UPC                       | 074983914937   |



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

15152 E Fremont Dr  
80112-0000, CO Centennial  
Phone: 720-278-7555  
Fax: 720-259-8851

## Taxonomies, Classifications, and Categories

|      |             |
|------|-------------|
| Type | Heat-Shrink |
|------|-------------|

## Packaging

|        |   |
|--------|---|
| Carton | 1 |
|--------|---|

|                 |      |
|-----------------|------|
| Weight Per roll | 6.11 |
|-----------------|------|

## Uses, Certifications, and Standards

|             |  |
|-------------|--|
| Application | For Dry Locations;Insulating and protecting wires and cables |
|-------------|--|

|          |   |
|----------|---|
| standard | Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770 |
|----------|---|