



HSTT2548Q Heatshrnk Tubing 1/4 BLK

Panduit Corporation

Catalog Number

HSTT2548Q

Manufacturer

Panduit Corporation

Description

The HSTT25-48-Q Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.25" Diameter X 4' Long (6.4 MM X 1.2 M). Color Black. 25 Per Package.

Weight per unit

1.1 (lbs/each)

Product Category

Insulating Materials

Features

flammability

Flame Retardant

media

Yes

outside diameter

0.25

Shrink Ratio

2:1

Material, Color, and Finish

Color

Black

Dimensions and Weight

Thickness

0.025

Descriptions

Description

HEATSHRNK TUBING 1/4 BLK

extra long description

PAN HSTT25-48-Q Dry-Shrink™ HSTT25-

Long Description

The HSTT25-48-Q Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1.

Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.25" Diameter x 4' Long (6.4 mm x 1.2 m). Color Black. 25 per package.

Product Type

Dry-Shrink™ HSTT25-48-Q Heatshrink, Black, Po, 4' L, 0.25" T



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

6112 42nd Street
79407-0000, TX Lubbock
Phone: 806-698-6329
Fax: 806-698-6805

Manufacturer Information

Brand	PANDUIT
GTIN	00074983905911
Manufacturers Part Number	HSTT25-48-Q
UPC	074983905911

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Type	Heat-Shrink

Packaging

Carton	25
Weight Per each	1.09

Uses, Certifications, and Standards

Application standard	For Dry Locations; Insulating and protecting wires and cables Mil Spec: AMS-DTL-23053/5 Class 1; UL: E122770
----------------------	---