

ELLIOTT ELECTRIC SUPPLY 2501 East 14th Avenue 67501-0000, KS Hutchinson Phone: 620-860-8405

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 620-860-8406



HSTT2548QC HT Shrink Tubing *Panduit Corporation*

Catalog Number	HSTT2548QC
Manufacturer	Panduit Corporation
Description	The HSTT25-48-QC Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect
	Against Abrasion. Applications Include Insulating and Protecting
	Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1.
	Temperature Range: -67°F to 275°F (-55°C to 135°C).
	Cross-Linked Polyolefin. 0.25" Diameter X 4' Long (6.4 MM X 1.2
	M). Color Clear. 25 Per Package.
Weight per unit	1.1 (lbs/each)
Product Category	Insulating Materials
Features	
flammability	N/A
media	Yes
outside diameter	0.25
Shrink Ratio	2:1
Material, Color, and Finish	
Color	Colorless
Dimensions and Weight	
Thickness	0.025
Descriptions	
Description	HT SHRINK TUBING
extra long description	PAN HSTT25-48-QC Dry-Shrink™ HSTT25
Long Description	The HSTT25-48-QC Thin Wall Heat Shrink Tubing shrinks around
	wires, connectors, joints, and terminals when heated to protect
	against abrasion. Applications include insulating and protecting
	wires/cables in indoor, dry locations. Shrink ratio: 2:1.
	Temperature range: -67°F to 275°F (-55°C to 135°C). Cross-linked
	polyolefin. 0.25" Diameter x 4' Long (6.4 mm x 1.2 m). Color
Product Typo	Clear. 25 per package. Dry-Shrink™ HSTT25-48-QC Heatshrink, Clear, Po, 4' L, 0.25"
Product Type	DI y-SHIHIK HST 125-40-QC HeatSHIHIK, Clear, PO, 4 L, 0.25



ELLIOTT ELECTRIC SUPPLY 2501 East 14th Avenue 67501-0000, KS Hutchinson

We Deliver...Lower Cost, Quality Products, & Personal Service

Phone: 620-860-8405 Fax: 620-860-8406

B 4			
$N/I \cap MI$	ufacturer	Intorm	1 tian
IVIALI	114111111111111111111111111111111111111		411CH
IVIGII	ai actai ci		utivii

Brand	PANDUIT	
GTIN	00074983906628	
Manufacturers Part Number	HSTT25-48-QC	
UPC	074983906628	

Taxonomies, Classifications, and Categories

Category Description	HEAT/COLD SHRINK
Туре	Heat-Shrink Tubing

Packaging

······································		
Carton	25	
Weight Per each	1.09	

Uses, Certifications, and Standards

Application	For Dry Locations; Insulating and protecting wires and cables
standard	Mil Spec: AMS-DTL-23053/5 Class 2