



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

6112 42nd Street  
79407-0000, TX Lubbock  
Phone: 806-698-6329  
Fax: 806-698-6805

## HSTT38C .375"X100' BLK Thin Wall HS *Panduit Corporation*

Catalog Number	HSTT38C
Manufacturer	Panduit Corporation
Description	The HSTT38-C Thin Wall Heat Shrink Tubing Shrinks Around Wires, Connectors, Joints, and Terminals When Heated to Protect Against Abrasion. Applications Include Insulating and Protecting Wires/Cables In Indoor, Dry Locations. Shrink Ratio: 2:1. Temperature Range: -67°F to 275°F (-55°C to 135°C). Flame Retardant, Cross-Linked Polyolefin. 0.375" Diameter X 100' Long (9.5 MM X 30.5 M). Color Black. 1 Roll.
Weight per unit	1.1 (lbs/each)
Product Category	Insulating Materials

### Features

flammability	Flame Retardant
media	Yes
outside diameter	0.37
Shrink Ratio	2:1

### Material, Color, and Finish

Color	Black
-------	-------

### Dimensions and Weight

Thickness	0.025
-----------	-------

### Descriptions

Description	.375"X100' BLK THIN WALL HS
extra long description	PAN HSTT38-C Dry-Shrink™ HSTT38-C H
Long Description	The HSTT38-C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.375" Diameter x 100' Long (9.5 mm x 30.5 m). Color Black. 1 roll.
Product Type	Dry-Shrink™ HSTT38-C Heatshrink, Black, Po, 100' L, 0.375" T

### Manufacturer Information

Brand	Panduit®
GTIN	00074983747047
Manufacturers Part Number	HSTT38-C
UPC	074983747047



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

6112 42nd Street  
79407-0000, TX Lubbock  
Phone: 806-698-6329  
Fax: 806-698-6805

## Taxonomies, Classifications, and Categories

Type ..... Heat-Shrink .....

## Packaging

Carton ..... 1 .....

Weight Per roll ..... 1.14 .....

## Uses, Certifications, and Standards

Application ..... For Dry Locations;Insulating and protecting wires and cables .....

standard ..... Mil Spec: AMS-DTL-23053/5 Class 1;UL: E122770 .....