



## CENTIUM ICN2S39T35I

No matter what the conditions require, operating at a variety of line voltages between 120V to 480V, whether located in high ambient temperature environments (requiring a 90° C rating) or not, our family of Philips Advance Centium ballasts are ideal for a wide variety of applications.

#### **Product data**

General Information		
Lamp Type	F39T5/HO	
Number of Lamps	1/2 piece/unit	
Ballast Type	Electronic Fluorescent	
Base Model	ICN2S39T	
Suitable For Outdoor Use	Yes	
Automatic Restart	Yes	
Operating and Electrical		
Input Voltage	120 to 277 V	
Input Frequency	50 to 60 Hz	
Total Harmonic Distortion USA	10 %	
Ignition Method	Programmed Start	
Crestfactor (Nom)	1.7	
Ignition Time (Nom)	1.5 s	
Ballast Factor (Nom)	1	
Power Factor (Nom)	0.98	
Input Current (Max)	0.73 A	
Input Current (Min)	0.31 A	
Input Power (Nom)	87-85 W	
Rated Lamp Power	39 W	

Wiring	
Color Input Terminals	Black and White
Color Output Terminals	RED, YEL & BLU
Wire Striplength	0.375 mm
Lamp Connection	Series
Wire Length by Color	No wires
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	Yes
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	20'
Max Ballast-Lamp Distance Tandem Wiring	Blue = 20'
Max Ballast-Lamp Distance Through Wiring	Blue = 20'
Connector Type	Poke-In
Temperature	
T-Case Maximum (Nom)	70 °C
Mechanical and Housing	
Housing Material	Metal
Housing	Т

Housing Dimensions	14.17" x 1.18" x 1.06"		
Approval and Application			
EMC Immunity Standard	FCC Non-Consumer		
Approval Marks	CSA certificate UL certificate RoHS Complia		
Hum And Noise Level	A		
UL Recognized	No		
Product Data			
Order product name	CENTIUM ICN2S39T35I		

EAN/UPC - Product	781087131756
Order code	913701253201
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	913701253201
Net Weight (Piece)	0.441 kg

### **Dimensional drawing**



Product	A1	A2	B1	C1
CENTIUM ICN2S39T35I	14.17 in	13.78 in	1.18 in	1.06 in



© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2017, May 26 - data subject to change





## CENTIUM ICN2S39T35I

No matter what the conditions require, operating at a variety of line voltages between 120V to 480V, whether located in high ambient temperature environments (requiring a 90° C rating) or not, our family of Philips Advance Centium ballasts are ideal for a wide variety of applications.

#### **Product data**

General Information		
Lamp Type	F39T5/HO	
Number of Lamps	1/2 piece/unit	
Ballast Type	Electronic Fluorescent	
Base Model	ICN2S39T	
Suitable For Outdoor Use	Yes	
Automatic Restart	Yes	
Operating and Electrical		
Input Voltage	120 to 277 V	
Input Frequency	50 to 60 Hz	
Total Harmonic Distortion USA	10 %	
Ignition Method	Programmed Start	
Crestfactor (Nom)	1.7	
Ignition Time (Nom)	1.5 s	
Ballast Factor (Nom)	1	
Power Factor (Nom)	0.98	
Input Current (Max)	0.73 A	
Input Current (Min)	0.31 A	
Input Power (Nom)	87-85 W	
Rated Lamp Power	39 W	

Wiring	
Color Input Terminals	Black and White
Color Output Terminals	RED, YEL & BLU
Wire Striplength	0.375 mm
Lamp Connection	Series
Wire Length by Color	No wires
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	Yes
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	20'
Max Ballast-Lamp Distance Tandem Wiring	Blue = 20'
Max Ballast-Lamp Distance Through Wiring	Blue = 20'
Connector Type	Poke-In
Temperature	
T-Case Maximum (Nom)	70 °C
Mechanical and Housing	
Housing Material	Metal
Housing	Т

Housing Dimensions	14.17" x 1.18" x 1.06"		
Approval and Application			
EMC Immunity Standard	FCC Non-Consumer		
Approval Marks	CSA certificate UL certificate RoHS Complia		
Hum And Noise Level	A		
UL Recognized	No		
Product Data			
Order product name	CENTIUM ICN2S39T35I		

EAN/UPC - Product	781087131756
Order code	913701253201
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	913701253201
Net Weight (Piece)	0.441 kg

### **Dimensional drawing**



Product	A1	A2	B1	C1
CENTIUM ICN2S39T35I	14.17 in	13.78 in	1.18 in	1.06 in



© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2017, May 26 - data subject to change