



ICS621 Insulated Serv. Entr. Sleeve

Abb Installation Products, Inc

Catalog Number	ICS621
Manufacturer	Abb Installation Products, Inc
Description	Aluminum 2-25/32 Inch Service Entrance Compression Splice For Wire Range - End A: 6 Ascr, 6 Stranded, 4 Solid, Blue, End B: 10 Stranded, 8 Solid, Brown, Die: 5/8. For Al to Al and Al to Cu Conductors.
Weight per unit	0.0580 (lbs/each)
Product Category	Large Terminals & Connectors

Features

connection	Compression
insulation	Yes
Material	Aluminum
Number of Conductors	2

Dimensions and Weight

Size	2-25/32 inch
------	--------------

Descriptions

Description	INSULATED SERV.ENTR.SLEEVE
extra long description	ABB ICS62-1 AL SERV ENTR SPLICE A:4
Long Description	Aluminum 2-25/32 inch Service Entrance Compression Splice for Wire Range - End A: 6 ASCR, 6 Stranded, 4 Solid, Blue, End B: 10 Stranded, 8 Solid, Brown, Die: 5/8. For AL to AL and AL to CU Conductors.

Product Type	AI Serv Entr Splice A:4SLD B:8SLD
--------------	-----------------------------------

Special Features	Constructed from Aluminum for High Conductivity. Solid Center Barriers and large Chamfers for easy cable insertion. Tough Stabilized nylon sleeves resist installing tool Pressure and provide Reliable 600 V Insulation. Prefilled with Oxide Inhibitor to prevent Oxidation and keep out moisture. All Splices are Color Coded and Marked with trip lengths, Installation Die Codes and Compression Locations, Providing easy Identification for easy Installation. Splices have Colored End Caps to make Identification
------------------	--

Manufacturer Information

Brand	Blackburn Mechanical
GTIN	00783786102341
Manufacturers Part Number	ICS62-1
UPC	783786102341



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7604 Gateway Blvd
77521-0000, TX Baytown
Phone: 832-514-7819
Fax: 832-514-7820

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Compression Splice Service Entrance

Packaging

Carton	100
Package	500
Weight Per each	0.058

Uses, Certifications, and Standards

Application	For Standard Conductor Splice
environmental conditions	All Seasons / Conditions
Mounting	None
standard	RUS Accepted. Complies with ANSI C119.4 when properly installed on Aluminum-to-Aluminum or Aluminum-to-Copper Conductors / RUS Accepted. Complies with ANSI C119.4 when properly installed on Aluminum-to-Aluminum or Aluminum-to-Copper Conductors