

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



ICS771 1/0 to 1 Ins Splice Abb Installation Products, Inc

Catalog Number	ICS771		
Manufacturer	Abb Installation Products, Inc		
Description	Aluminum 2-25/32 Inch Service Entrance Compression Splice For		
	Wire Range - End A: 1/0 Ascr, 1/0, Yellow, End B: 2 Ascr, 1-2		
	Stranded, Red, Die: 5/8. For AI to AI and AI to Cu Conductors.		
Weight per unit			
Product Category	Large Terminals & Connectors		
eatures			
connection	Compression		
insulation	Yes		
Material	Aluminum		
Number of Conductors	2		
imensions and Weight			
Size	2-25/32 inch		
escriptions			
Description	1/0 TO 1 INS SPLICE		
extra long description	ABB ICS77-1 INSULATED SERV. ENTR.SL		
Long Description	Aluminum 2-25/32 inch Service Entrance Compression Splice for		
	Wire Range - End A: 1/0 ASCR, 1/0, Yellow, End B: 2 ASCR, 1-2		
	Stranded, Red, Die: 5/8. For AL to AL and AL to CU Conductors.		
Product Type	Insulated Serv. Entr.Sleeve		
Special Features	Constructed from Aluminum for High Conductivity. Solid Center		
	Barriers and large Chamfers for easy cable insertion. Tough		
	Stabilized nylon sleebes resist installing tool Pressure and provid		
	Reliable 600 V Insulation. Prefilled with Oxide Inhibitor to		
	prevent Oxidation and keep out moisture. All Splices are Color Coded and Marked with trip lengths, Installation Die Codes and		
	Compression Locations, Providing easy Identification for easy		
	Installation. Splices have Colored End Caps to make		
	Identification		
lanufacturer Information			
Brand	Blackburn Mechanical		
GTIN	00783786102405		
Manufacturers Part Number	ICS77-1		
UPC	783786102495		
axonomies, Classifications, and (Categories		
Category Description	Comp & Mach Lugs and Dutt Splices		
J. J. Market Market Street			



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

- J J		
Carton	100	
Package	500	
Weight Per each	0.045	

Uses, Certifications, and Standards

Application	For Standard Conductor Splice		
environmental conditions	All Seasons / Conditions		
Mounting	None		
standard	RUS Accepted. Complies with ANSI C119.4 when properly installed on Aluminum-to-Aluminum or Aluminum-to-Copper Conductors / RUS Accepted. Complies with ANSI C119.4 when properly installed on Aluminum-to-Aluminum or Aluminum-to-Copper Conductors		