



Surge Protection: Whole House Surge Protection

Smart Guard® Whole House Surge Protective Device with IModule™ | IG2240-IMSK

Smart Guard® Whole House Surge Protective Device with IModule™ IG2240-IMSK

Intermatic's Smart Guard® Whole House Surge Protective Device provides coverage of your customer's big investment equipment, from appliances and computers, to HVAC equipment and TVs. This innovative SPD uses the IModule™ with LED lights for quick and easy indication when protection has been compromised. A blue light indicates the SPD unit is ON and a green light indicates surge protection is active. Trusted, state-of-the-art TPMOV® (Thermally Protected Metal Oxide Varistor) surge protection technology eliminates the potentially hazardous failure modes that are commonly associated with standard MOV technology. Type 1 applications include outdoor installations before service entrances and utility meter cabinets. Type 2 applications include installations after service entrances. UL Listed to ANSI/UL 1449 3rd edition



Features & Applications

Features

- Six Modes of protection
- TPMOV® surge protection technology
- Module Power Switch, included on IG2240-IMSK, enables convenient disconnection of power at the SPD when replacing IModules
- Includes three IModules with LED power and protection status lights
- IModules replace quickly and easily, eliminating the need to install a new SPD unit


Applications

- Residential
- Light Commercial

- Tamper-proof IModule doors, will only open when IModule is being inserted
- Includes the IG2200-FMK flush mount kit
- Type 1 Enclosure for indoor applications in metal
- 10-year product warranty
- \$50,000 connected equipment warranty for 10 years on appliances and electronics
- UL certified to ANSI/UL 1449 3rd edition

System Includes

System Includes (1)



IG2200-FMK

**FLUSH MOUNT KIT FOR IG2240-IMSK AND
IG2280-IM**

Qty: 1

Specifications

Surge Protection Type

9/20/2018	IG2240-IMSK - Intermatic	
1, 2	Maximum Continuous Operating Voltage (L-N)	Operating Temperature Min (°C)
Nominal Discharge Current	150	-35
10 kA	Maximum Continuous Operating Voltage (N-G)	Operating Temperature Min (F)
Short Circuit Current Rating	150	-31
10 kA	Voltage Protection Rating (L-G)	Number of Wire Leads
Surge Protection	1500	4
TPMOV®	Voltage Protection Rating (L-L)	Wire Lead Length (in)
Wiring Option	1500	32
Terminals, Wire Leads	Voltage Protection Rating (L-N)	Wire Lead Length (mm)
Enclosure Type	800	812.8
Indoor Type 1 Metal	Voltage Protection Rating (N-G)	Warranty
Maximum Continuous Operating Voltage (L-G)	700	10-year
300	Operating Temperature Max (°C)	Connect Equipment Warranty Period
Maximum Continuous Operating Voltage (L-L)	85	10-year
300	Operating Temperature Max (F)	
	185	

Videos

Related Accessories and Parts (1)



IModule™ Replacement Module for
Smart Guard

IG120RSM10K



Copyright © 2017 Intermatic Incorporated. All rights reserved.



Surge Protection: Whole House Surge Protection

Smart Guard® Whole House Surge Protective Device with IModule™ | IG2240-IMSK

Smart Guard® Whole House Surge Protective Device with IModule™ IG2240-IMSK

Intermatic's Smart Guard® Whole House Surge Protective Device provides coverage of your customer's big investment equipment, from appliances and computers, to HVAC equipment and TVs. This innovative SPD uses the IModule™ with LED lights for quick and easy indication when protection has been compromised. A blue light indicates the SPD unit is ON and a green light indicates surge protection is active. Trusted, state-of-the-art TPMOV® (Thermally Protected Metal Oxide Varistor) surge protection technology eliminates the potentially hazardous failure modes that are commonly associated with standard MOV technology. Type 1 applications include outdoor installations before service entrances and utility meter cabinets. Type 2 applications include installations after service entrances. UL Listed to ANSI/UL 1449 3rd edition



Features & Applications

Features

- Six Modes of protection
- TPMOV® surge protection technology
- Module Power Switch, included on IG2240-IMSK, enables convenient disconnection of power at the SPD when replacing IModules
- Includes three IModules with LED power and protection status lights
- IModules replace quickly and easily, eliminating the need to install a new SPD unit


Applications

- Residential
- Light Commercial

- Tamper-proof IModule doors, will only open when IModule is being inserted
- Includes the IG2200-FMK flush mount kit
- Type 1 Enclosure for indoor applications in metal
- 10-year product warranty
- \$50,000 connected equipment warranty for 10 years on appliances and electronics
- UL certified to ANSI/UL 1449 3rd edition

System Includes

System Includes (1)



IG2200-FMK

**FLUSH MOUNT KIT FOR IG2240-IMSK AND
IG2280-IM**

Qty: 1

Specifications

Surge Protection Type

9/20/2018	IG2240-IMSK - Intermatic	
1, 2	Maximum Continuous Operating Voltage (L-N)	Operating Temperature Min (°C)
Nominal Discharge Current	150	-35
10 kA	Maximum Continuous Operating Voltage (N-G)	Operating Temperature Min (F)
Short Circuit Current Rating	150	-31
10 kA	Voltage Protection Rating (L-G)	Number of Wire Leads
Surge Protection	1500	4
TPMOV®	Voltage Protection Rating (L-L)	Wire Lead Length (in)
Wiring Option	1500	32
Terminals, Wire Leads	Voltage Protection Rating (L-N)	Wire Lead Length (mm)
Enclosure Type	800	812.8
Indoor Type 1 Metal	Voltage Protection Rating (N-G)	Warranty
Maximum Continuous Operating Voltage (L-G)	700	10-year
300	Operating Temperature Max (°C)	Connect Equipment Warranty Period
Maximum Continuous Operating Voltage (L-L)	85	10-year
300	Operating Temperature Max (F)	
	185	

Videos

Related Accessories and Parts (1)



IModule™ Replacement Module for
Smart Guard
IG120RSM10K



Copyright © 2017 Intermatic Incorporated. All rights reserved.