



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1732 South Business 287  
75110-0000, TX Corsicana  
Phone: 903-872-9696  
Fax: 903-872-9980



## IKL69 Ins Service Entry Sleeve

*Abb Installation Products, Inc*

Catalog Number	IKL69
Manufacturer	Abb Installation Products, Inc
Description	Aluminum 4 Inch Service Entrance Compression Splice For Wire Range - Pink End: 4/0 Ascr, 4/0 STR, 250 CPT, 4/0 CPR. Pink End: 4/0 Ascr, 4/0 STR, 250 CPT, 4/0 CPR. Installing Dies: TX 249 840 (Eei 11A). Compound and Capped. Includes 5-7/16 Inch Sleeve
Weight per unit	0.1550 (lbs/each)
Product Category	Large Terminals & Connectors

### Features

connection	Compression
insulation	Yes
Material	Aluminum
Number of Conductors	2

### Dimensions and Weight

Size	Splice 4 inch, Sleeve 5-1/2 inch
------	----------------------------------

### Descriptions

Description	INS SERVICE ENTRY SLEEVE
extra long description	ABB IKL69 AL SERVENTR SPLICE A:4/0
Long Description	Aluminum 4 inch Service Entrance Compression Splice for Wire Range - Pink End: 4/0 ASCR, 4/0 STR, 250 CPT, 4/0 CPR. Pink End: 4/0 ASCR, 4/0 STR, 250 CPT, 4/0 CPR. Installing Dies: TX 249 840 (EEI 11A). Compound and Capped. includes 5-7/16 inch Sleeve
Product Type	Al Serventr Splice A:4/0 B:4/0 5.5
Special Features	Pre-insulated for fast, easy installation of large home or commercial service entrances. Concave polyethylene end caps seal out dirt, but are easily pierced when inserting conductor

### Manufacturer Information

Brand	Blackburn Mechanical
GTIN	00783786050383
Manufacturers Part Number	IKL69
UPC	783786050383

### Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Type	Compression Splice Service Entrance



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1732 South Business 287  
75110-0000, TX Corsicana  
Phone: 903-872-9696  
Fax: 903-872-9980

## Packaging

Carton	25
Package	100
Weight Per each	0.155

## Uses, Certifications, and Standards

Application	For Combinations of Aluminum-to-Aluminum and Aluminum-to-Copper Conductors. Use as a low tension reducing sleeve for Insulated Conductor
environmental conditions	All Seasons / Conditions
Mounting standard	None RUS Listed. Passes the Requirements of ANSI C119.4 / RUS Listed. Passes the Requirements of ANSI C119.4