

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



IPLMD2503 250-#6 3 Pole Polaris Connector Block W/MTG Holes *Nsi Industries*

IPLMD2503		
Nsi Industries		
The Polaris IPLMD250-3 Multi-Tap Mountable Dual-Sided Entry Connector Features 3 Ports Sized For 250 MCM - 6 Awg Wires. Mounting Holes On Either Side Of The Connector Allow For Direct Mounting to Troughs, Panels or Wireways With 1/4€ Bolts. The Body Is Made From Aluminum Alloy Wrapped In A Layer Of Plastisol Insulation. Each Dual-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Installs With A Hex Key and Torque Wrench, With		
0.5900 (lbs/each)		
Large Terminals & Connectors		
3		
1		
600 V		
1 YEAR		
250 MCM-6 AWG		
Class B & C		
Black		
Plastisol Insulated		
Aluminum		
L=4.420 - W=2.280 - H=2.370		



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

			•				
1 14	\mathbf{r}	cr	ın	т.	$\boldsymbol{\wedge}$	nc	۰
D	_				L J	117	١

environmental conditions

standard

Description	250-#6 3 POLE POLARIS CONNECTOR BLOCK W/MTG HOLES		
extra long description	NSI IPLMD250-3 POLARIS Mount Ins Mu		
Features	The Polaris IPLMD250-3 3-Port Dual-Sided Mountable Connector provides the simplest solution for forming a secure connection between up to three conductors in applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 250 MCM - 6 AWG wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated connector options using just a hex key and torque wrench. Mountable connectors feature 1/4" mounting hol		
Long Description	The Polaris IPLMD250-3 Multi-Tap Mountable Dual-Sided Entry Connector features 3 ports sized for 250 MCM - 6 AWG wires. Mounting holes on either side of the connector allow for direct mounting to troughs, panels or wireways with 1/4†bolts. The body is made from aluminum alloy wrapped in a layer of plastisol insulation. Each dual-sided port is pre-loaded with an oxide inhibitor, with removable access plugs over the hex screws used to tighten the connections. Installs with a hex key and torque wrench, with		
Product Type	Polaris Mount Ins Multi-Tap 250 3 Port		
Special Features	(3) 250 MCM-6 AWG - Dual Rated - With Mounting Holes		
Manufacturer Information			
Brand	Polaris		
GTIN	00662381943019		
Manufacturers Part Number	IPLMD250-3		
UPC	662381943019		
Taxonomies, Classifications, and G	Categories		
Category Description	SPLIT BOLTS		
Туре	Double Sided Entry With Mounting Holes		
Packaging			
Carton	2		
Weight Per each	0.59		
Uses, Certifications, and Standard	ls		
	Wire Termination		
	00.0		

90 C

UL 486A/B