



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1715 South Knoxville
72802-0000, AR Russellville
Phone: 479-967-2303
Fax: 479-967-2306



IR3000FC Connector, Infrared, FC *Fluke Electronics*

Catalog Number	IR3000FC
Manufacturer	Fluke Electronics
Description	Connect Your Fluke Test Tool With The IR3000 FC Connector and Get All The Benefits Of The Fluke Connect Mobile App. Fluke Connect With Sharelive™ Video Call Is The Only Wireless Measurement System That Lets You Stay In Contact With Your Entire Team Without Leaving The Field. The Fluke Connect™ Mobile App Is Available For Android™ and Ios Smart Phones and Works With Over 20 Different Fluke Products—The Largest Suite Of Connected Test Tools In The World. and There Is More On The Way.
Weight per unit	0.3000 (lbs/each)
Product Category	Fiber-Optic Connectors

Material, Color, and Finish

Color	Gray
-------	------

Descriptions

Description	CONNECTOR, INFRARED, FC
extra long description	FLK FLUKE-IR3000FC IR 3000 CONN FOR
Long Description	Connect your Fluke test tool with the ir3000 FC connector and get all the benefits of the Fluke Connect Mobile App. Fluke Connect with ShareLive™ video call is the only wireless measurement system that lets you stay in contact with your entire team without leaving the field. The Fluke Connect™ mobile app is available for Android™ and iOS smart phones and works with over 20 different Fluke products—the largest suite of connected test tools in the world. And there is more on the way.
Product Type	Ir 3000 Conn For 189 289 789

Manufacturer Information

Brand	FLUKE
GTIN	00095969723855
Manufacturers Part Number	FLUKE-IR3000FC
UPC	095969723855

Taxonomies, Classifications, and Categories

Category Description	TEST EQUIPMENT, TESTERS AND MULTIMETERS
----------------------	---

Packaging

Carton	1
Weight Per each	0.3



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1715 South Knoxville
72802-0000, AR Russellville
Phone: 479-967-2303
Fax: 479-967-2306

Uses, Certifications, and Standards

Enclosure	Hard plastic
environmental conditions	Temperature---Operating: -10 ?°C to 50 ?°C, Storage: -20 ?°C to 60 ?°C
Mounting	PLUG IN