



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

308 Centennial Boulevard  
73013-0000, OK Edmond  
Phone: 405-562-6283  
Fax: 405-562-6284



## JDL150 150A 600V Class J Time Delay Fuse

*Edison Fuses*

Catalog Number	JDL150
Manufacturer	Edison Fuses
Description	Eaton Edison Series JDL Fuse, Time-Delay Current-Limiting Fuse, Non-Indicating, 150 A, Dual, J, Non-Indicating, 200 Kaic, 5, 600 V
Weight per unit	0.8000 (lbs/each)
Product Category	Dual Element

### Features

amperage rating	150
dimensions	5.7500 IN X 1.6300 IN X 1.6300 IN
Fuse Class	Class J
interrupt rating	200 kAIC
media	Yes
Voltage Rating	600 V

### Descriptions

Description	150A 600V CLASS J TIME DELAY FUSE
extra long description	EFSE JDL150 UL CLASS J TIME DELAY 6
Features	Edison's UL Class J fuse products are offered in both Dual-Element Time-Delay (JDL) and Fast-Acting (JFL) types. Both types have 200,000 amp interrupting rating at 600Vac RMS Sym amps. Their small physical size and high performance characteristics makes Class J fuses ideal for any space-limited applications. Edison's JFL fuses are best suited for the protection of non-inductive loads such as resistive heating and lighting circuits.
Long Description	Eaton Edison series JDL fuse, Time-delay current-limiting fuse, Non-indicating, 150 A, Dual, J, Non-indicating, 200 kAIC, 5, 600 V
Product Type	UI Class J Time Delay 600
Special Features	Non-Indicating

### Manufacturer Information

Brand	Eaton
GTIN	00782634803522
Manufacturers Part Number	JDL150
UPC	782634803522

### Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

308 Centennial Boulevard  
73013-0000, OK Edmond  
Phone: 405-562-6283  
Fax: 405-562-6284

## Packaging

Carton	1
Weight Per each	0.8

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	RoHS Compliant,CE Marked