

ELLIOTT ELECTRIC SUPPLY 4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 806-220-0811



K075 3/4 Liq-Tite Conn Hubbell--Killark

Catalog Number	K075
Manufacturer	HubbellKillark
Description	3/4" Straight Liquidtight Connector Non-Insulated
Weight per unit	6.0 (lbs/each)
Product Category	Liquid Tight Fittings

Features

insulation	False
Insulation Type	Non-Insulated
Material	Staal

Material, Color, and Finish

Color	Gray
Finish	Zinc Plated

Dimensions and Weight

Length	1-3/8
Width	1-9/16

Descriptions

Description	3/4 LIQ-TITE CONN
extra long description	KLRK K075 3/4" STR LT CONNECTOR NO
Long Description	3/4" Straight Liquidtight Connector Non-Insulated
Product Type	3/4" STR LT Connector Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

Manufacturer Information

Brand	KILLARK
GTIN	00783936997940
Manufacturers Part Number	K075
series	K Series
UPC	783936997940

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Straight Liquidtight Non-Insulated Connector

Packaging

okugirig		
Carton	1	
Package	25	
Weight Per each	6	
•		

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4000 Mockingbird Ln 79109-3210, TX Amarillo Phone: 806-220-0404

Fax: 806-220-0811

Uses, Certifications, and Standards

Application	Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location
environmental conditions	Hazardous locations
standard	UL, CSA