



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



K0759 3/4 90D Liq-Tite Conn

Hubbell--Killark

| | |
|------------------|--|
| Catalog Number | K0759 |
| Manufacturer | Hubbell--Killark |
| Description | 3/4" 90° Liquidtight Connector Non-Insulated |
| Weight per unit | 9.3 (lbs/each) |
| Product Category | Liquid Tight Fittings |

Features

| | |
|-----------------|---------------|
| insulation | False |
| Insulation Type | Non-Insulated |
| Material | Steel |

Material, Color, and Finish

| | |
|--------|-------------|
| Color | Gray |
| Finish | Zinc Plated |

Dimensions and Weight

| | |
|--------|---------|
| Length | 1-15/16 |
| Width | 1-3/8 |

Descriptions

| | |
|------------------------|--|
| Description | 3/4 90D LIQ-TITE CONN |
| extra long description | KLRK K0759 3/4" 90° LT CONNECTOR NO |
| Long Description | 3/4" 90° Liquidtight Connector Non-Insulated |
| Product Type | 3/4" 90° LT Connector Non-Insulated |
| Special Features | Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc. |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | KILLARK |
| GTIN | 00783936991177 |
| Manufacturers Part Number | K0759 |
| series | K Series |
| UPC | 783936991177 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | FORM 5 CONDULETS, COVERS, & GASKETS |
| Type | 90 Degree Liquidtight Non-Insulated Connector |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 25 |
| Weight Per each | 9.25 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location

environmental conditions
standard

Hazardous locations
UL, CSA