

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 936-560-4685



K100 1-In STR Liq-Tite Conn Hubbell--Killark

Catalog Number	K100
Manufacturer	HubbellKillark
Description	1" Straight Liquidtight Connector Non-Insulated
Weight per unit	3.4 (lbs/each)
Product Category	Liquid Tight Fittings

Features

insulation	False	
Insulation Type	Non-Insulated	
Material	Stool	

Material, Color, and Finish

Color	Gray
Finish	Zinc Plated

Dimensions and Weight

3	
Length	1-11/16
Width	1-11/16

Descriptions

Description	1-IN STR LIQ-TITE CONN
extra long description	KLRK K100 1" STR LT CONNECTOR NON-I
Long Description	1" Straight Liquidtight Connector Non-Insulated
Product Type	1" STR LT Connector Non-Insulated
Special Features	Liquidtight fittings are used with metallic and non-metallic conduit to seal out water, oil, and dust in applications food processors, beverage & chemical plants, plastics fabricators, machine shops, etc.

Manufacturer Information

Brand	KILLARK
GTIN	00783936998497
Manufacturers Part Number	K100
series	K Series
UPC	783936998497

Taxonomies, Classifications, and Categories

Category Description	FORM 5 CONDULETS, COVERS, & GASKETS
Туре	Straight Liquidtight Non-Insulated Connector

Packaging

maging			
Carton	1		
Package	10	 	
Weight Per each	3.4	 	
<u> </u>			

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Use with metallic and non-metallic conduit to seal out water, oil, and dust in applications for food processors, beverage and chemical plants, plastics fabricators, machine shops, etc. Liquidtight connectors are also suitable for use in hazardous location
environmental conditions	Hazardous locations
standard	UL, CSA