



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4300 Danhill Drive
76801-0000, TX Brownwood
Phone: 325-646-6566
Fax: 325-646-3777



KA30U 6-300 Cu/Al 1 Conductor Lug

Burndy LLC

| | |
|------------------|---|
| Catalog Number | KA30U |
| Manufacturer | Burndy LLC |
| Description | Aluminum Universal Terminal, 1 Hole, 6 Awg (STR)-300 Kcmil, 5/16" Stud, 1 Screw, Al/Cu Rated, Tin Plated. |
| Weight per unit | 0.0800 (lbs/each) |
| Product Category | Large Terminals & Connectors |

Features

| | |
|----------------------|----------|
| Material | Aluminum |
| Number of Conductors | 1 |
| pallet quantity | 8800 |

Descriptions

| | |
|------------------------|---|
| Description | 6-300 CU/AL 1 CONDUCTOR LUG |
| extra long description | BUR KA30U 6STR-300 DUAL RATED |
| Long Description | Aluminum Universal Terminal, 1 Hole, 6 AWG (Str)-300 kcmil, 5/16" Stud, 1 Screw, Al/Cu Rated, Tin Plated. |
| Product Type | Terminal |
| Special Features | Features: These Dual-Rated One-Conductor Lugs Are Constructed From High Strength Aluminum Alloy And Electro Tin-Plated To Provide Low Contact Resistance, Stud/bolt Hole Size: 1/4 IN, Set Screw Type: Allen Key, Length: 2 IN, Installation Torque: 275 IN-LB, Width: 1 IN, Height: 1.12 IN, Dimension D: 0.94 IN, Dimension N: 0.5 IN, Dimension T: 0.25 IN |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | BURNDY |
| GTIN | 00781810370223 |
| Manufacturers Part Number | KA30U |
| UPC | 781810370223 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-----------------------------------|
| Category Description | Comp & Mech Lugs and Butt Splices |
| Type | Bolted Lugs & Terminals |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 25 |
| Weight Per each | 0.08 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4300 Danhill Drive
76801-0000, TX Brownwood
Phone: 325-646-6566
Fax: 325-646-3777

Uses, Certifications, and Standards

| | |
|--------------------|------------------------------------|
| Application | For Aluminum And Copper Conductors |
| standard | UL 486A-486B |
| Temperature Rating | 194 |