

ELLIOTT ELECTRIC SUPPLY 1732 South Business 287 75110-0000, TX Corsicana Phone: 903-872-9696 Fax: 903-872-9980



KTKR2 2A 600V Fa Class CC Fuse Bussmann Fuses

_	
Catalog Number	KTKR2
Manufacturer	Bussmann Fuses
Description	Fuse, Fast Acting Fuse Speed, Class CC Fuse, Ferrule End X Ferrule End Connection, 2 A, 600 V Ac, Melamine Tube Material, 0.41 In Diameter, 1.5 In Overall Length, 0.02 LB
Weight per unit	0.0200 (lbs/each)
Product Category	Small Dimension Fuses
Features	
amperage rating	2
class	CC
Coil Voltage	Elec Assemblies, Panels & EOEM - Elec Assemblies/Panels/EOEMs - AftermarketElec Assemblies, Panels & EOEM - Control Panels for MachinesInd Facilities & Factories - Facility: Power Distribution and ControlElec Assemblies, Panels & EOEM - Electrical Assemblies and EOEMs - OtherStationary Mach Equip In Factory - RoboticsElec Assemblies, Panels & EOEM - Panel BuildersElec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
connection	Ferrule end x ferrule endFerrule
dimensions	1.5000 IN X 0.3750 IN X 0.3750 IN
media	Yes
Material, Color, and Finish	
Color	Auto
Dimensions and Weight	
Depth	1.5
Size	13/32 In Diameter X 1-1/2 In Length
Width	0.41



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1732 South Business 287 75110-0000, TX Corsicana Phone: 903-872-9696 Fax: 903-872-9980

_			•			
. 1	es	~r	ın		$\boldsymbol{\wedge}$	nc
	_	L		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		117
_	-	v.			•	

Description	2A 600V FA CLASS CC FUSE
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Special Features	Rejection Style
Manufacturer Information	
Brand	Cooper Bussmann North America
GTIN	00051712420600
sub brand	Ind Facilities & Factories - Facility: Safety and Security Systems

Taxonomies, Classifications, and Categories

051712420600

Category Description	MIDGET FUSES
Type	FUSE

Trade Size

UPC

ć	aperture size	Ind	Facili	ities d	&	Factories -	Facility:	Safety	/ and	Security	Systems	

Packaging

Carton	10
Weight Per each	0.02

Uses, Certifications, and Standards

standard	UL 248-4, CSA C22.2, CE