



KT-LED27HID-EX39-840-D /G2

HID REPLACEMENT LED LAMP

DESCRIPTION

27W HID Replacement LED Lamp | 4000K | >80 CRI | IP64 Rated













PRODUCT FEATURES

- Replacement for Conventional Metal Halide Lamp
- Non-Dimmable; Do Not Dim
- 50,000+ Hour Lifetime
- Environmentally Friendly: No Mercury Used
- Instant Startup
- UL Listed
- Operating Temperature: -29°C/-20°F to 60°C/140°F
- Integral Driver, Eliminates the Need for External Driver or Ballast; Includes 4kV Surge Protection
- IP64 Rated; Integrated Heat Sink Quickly Dissipates Heat and Guides Water Intrusion Out of the Lamp
- Suitable for use in fully enclosed fixture. Minimum lamp compartment dimensions: 6in x 6in x 7.3in

OPERATING SPECIFICATIONS

ELECTRICAL CHARACTERISTICS

Input Voltage	Power Consumption	Power Factor	Input Current
120-277Vac	27W	>0.9	0.23A @ 120V 0.10A @ 277V


RATED LIFE

L70 (Hours)	50,000


PHOTOMETRIC CHARACTERISTICS

Color Temperature (CCT)	4000K	
Luminous Flux	3780 lm	
Color Rendering Index (CRI)	>80	
Efficacy	140 lm/W	
Visible Light Area	360º	

SPECTRAL DISTRIBUTION



LUX DISTANCE CURVE









KT-LED27HID-EX39-840-D/G2

HID REPLACEMENT LED LAMP



E39 MOGUL SOCKET



EX39-based lamps will work in both E39 and EX39 sockets.

WIRING DIAGRAM

STFP 1

Disconnect power. Disconnect and remove existing ballast, capacitor, and/or ignitor (where applicable) from fixture.


STEP 2

Rewire for line voltage to the lamp socket. Lamp is compatible with 120-277V from single phase, three phase wye, and three phase delta systems.

STEP 3


Install new LED replacement lamp. Ensure lamp is






*or other line for certain three phase systems such as 120/208 three phase wye systems

PHYSICAL CHARACTERISTICS





LAMP DIMENSIONS

A (Illuminated Length)	3.42"	
B (Body Length)	7.37"	
C (Diameter)	2.36"	

BASE TYPE: EX39 (Mogul)

ORDERING INFORMATION

ORDER CODE	PACKAGING STYLE	PACK QTY.	ITEM STATUS
KT-LED27HID-EX39-840-D/G2-DP	Distributor Pack (Individual Cartons)	16	Quick Ship

CATALOG NUMBER BREAKDOWN

