

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5500 Wheeler Avenue 72901-0000, AR Fort Smith Phone: 479-648-1902 Fax: 479-648-1960



Weight Per each

LB250M 2-1/2" LB FM5 Conduit Body *Crouse-Hinds*

| Catalog Number | LB250M |
|---------------------------------|---|
| Manufacturer | Crouse-Hinds |
| Description | Conduit Body, Electrogalvanized With Aluminum Acrylic Paint, Form 5 Body Type, 2-1/2 In Trade Size, Threaded Connection, LB Shape, Back Cable Entry, 2 Hubs, 2-1/2 In Hub Size, 90° Hub Location, LB Configuration, 13.6 In Length, 4.31 In Width, 5.4 In Height, Threaded, 11.8 LB/Ea |
| Weight per unit | |
| Product Category | Bodies & Covers |
| Features | |
| dimensions | 13.6000 IN X 4.3100 IN X 5.4000 IN |
| Form | Form 5 |
| Dimensions and Weight | |
| Hub Size | 2-1/2 in |
| Length | 13.60 |
| Descriptions | |
| Description | 2-1/2" LB FM5 CONDUIT BODY |
| extra long description | CRS-H LB250M 2-1/2 FORM 5 LB COND B |
| Features | Form 5 malleable iron conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide access to conductors for maintenance and future system changes. Form 5 conduit bodies are manufactured in trade sizes 1/2" to 4", and are interchangeable with Appleton Form 35 conduit bodies. They are also available with a h |
| Manufacturer Information | |
| Brand | EATON CROUSE-HINDS SERIES |
| GTIN UPC | 00782274755991 |
| | 782274755991 |
| Taxonomies, Classifications, an | |
| | FORM 5 CONDULETS, COVERS, & GASKETS Conduit outlet body |
| Type | Conduit outlet body |
| Packaging Carton | 1 |

11.8

5500 Wheeler Avenue 72901-0000, AR Fort Smith Phone: 479-648-1902 Fax: 479-648-1960

| Uses, (| Certificat | tions, and | Stand | lards |
|---------|------------|------------|-------|-------|
|---------|------------|------------|-------|-------|

| standard | UL 514B, CSA C22.2, CUL |
|----------|-------------------------|
|----------|-------------------------|